

Bidder acknowledges receipt of and has added to and made a part of the proposal and contract documents the following addendum (addenda):

ADDENDUM NO. <u>  1  </u>	DATED <u>  3/24/2005  </u>	ADDENDUM NO. _____	DATED _____
ADDENDUM NO. _____	DATED _____	ADDENDUM NO. _____	DATED _____

Number	Description
1	Add Document 00910.

TOTAL ADDENDA:   1    
(Must agree with total addenda issued prior to opening of bids)

Respectfully Submitted,

DATE \_\_\_\_\_

\_\_\_\_\_  
Contractor

BY \_\_\_\_\_  
Signature

TITLE \_\_\_\_\_

ADDRESS \_\_\_\_\_

(To be filled in if a corporation)

Our corporation is chartered under the Laws of the State of \_\_\_\_\_ and the names, titles and business addresses of the executives are as follows:

\_\_\_\_\_  
President Address

\_\_\_\_\_  
Secretary Address

\_\_\_\_\_  
Treasurer Address

The following is my (our) itemized proposal.

I (We) agree to complete the entire Project within the specified Contract Time.

**BIDDERS MUST OBTAIN ADDENDUM FROM MDOT CONTRACT ADMINISTRATION DIVISION TO BID.**

**MISSISSIPPI DEPARTMENT OF TRANSPORTATION**

**ADDENDUM No. 1  
DOCUMENT 00910**

**DATE:** 03-21-05

**PROJECT:** DISTRICT HEADQUARTERS BUILDING AT  
HATTIESBURG, FORREST COUNTY, MISSISSIPPI

**PROJECT NUMBER:** BWO-6098-18(001) 501427

PART 1 GENERAL

1.01 DESCRIPTION: Bidders are hereby advised that the following changes are to be made to this Contract. Bidders shall acknowledge receipt of this Addendum by inserting the accompanying page showing its number and date in the Proposal.

1.02 SPECIFICATIONS

- A. Document 00010 – Table of Contents. Omit this Section in its entirety and replace with Document 00010 – Table of Contents (Revised 03-21-05). Note: The Contract is to include all Site Work as shown on Drawings. The Department of Transportation will not be responsible for any site work.
- B. Section 01290 – Payment Procedures. Omit this Section in its entirety and replace with Section 01290 – Payment Procedures (Revised 3-21-05).
- C. Section 02365 – Soil Treatment for Termite Control. Omit this Section in its entirety and replace with Section 02365 – Soil Treatment for Termite Control. (Revised 3-21-05).
- D. Section 07218 – Spray-on Insulation System – Add this Section (3-21-05).
- E. Section 12492 – Horizontal Louver Blinds. Omit this Section in its entirety and replace with Section 12492 – Horizontal Louver Blinds. (Revised 3-21-05).
- F. Section 16420 – Emergency Electrical Generator:
  - 1. Point of clarification: This is a diesel generator and no gas is required.
  - 2. Sub-Section 1.03 A1. – Change 300kw / 375kva to 360kw / 450kva.

1.03 DRAWINGS

- A. Sheet Number 105, Working Number E4.1 – Light Fixture Schedule & Power Riser Diagram: (Revised 03-21-05). The following changes include:
  - 1. Change 800Amp MLO panel (EDP) to a 600 Amp MLO panel. Also, change feeder to EDP from 2 runs of 4#500MCM with #1/0 (G) in 3-1/2" conduit to 2 runs of 4#350 MCM with #1(G) in 3-1/2" conduit.

2. Change Automatic Transfer Switch (ATS) from an 800 Amp switch to a 600 Amp transfer switch. Change feeder to ATS from 2 runs of 4#500MCM with 1#1/0(G) in 3-1/2" conduit to 2 runs of 4#350MCM with 1#1(G) in 3-1/2" conduit (Revised 03-21-05).
- B. Sheet Number 97 – Working Number, E2.5 - Auditorium Floor Plan – Electrical (Revised 03-21-05). The following changes include:
1. The generator indicated on the lighting part of this sheet should read 350 KW just like the power/communications part of this sheet.
- C. Sheet Number 103, Working Number E3.3 – Electrical Panel Schedules (Revised 03-21-05). The following Change include:
1. Change breaker MDP-8,10,12 in panel MDP from an 400A3P breaker to an 600A3P breaker feeding panel EDP.
  2. Change breaker feeding elevator (MDP-7,9,11) from a 90A3P shunt trip breaker to a 60A3P shunt trip breaker.
- D. Sheet Number 95, Working Number E2.3 – First Floor Plan – Power/Communications (Revised 03-21-05). The following changes include:
1. Relocate Panels in Room 112 as required to minimize feeder runs and any interference with elevator pit wall.

PART 2 PRODUCTS  
Not Used

PART 3 EXECUTION  
Not Used

\*\*\*END OF DOCUMENT\*\*\*

# MISSISSIPPI DEPARTMENT OF TRANSPORTATION

## TABLE OF CONTENTS

DOCUMENT 00010

**PROJECT:** DISTRICT HEADQUARTERS BUILDING AT  
HATTIESBURG, FORREST COUNTY, MISSISSIPPI

**PROJECT NUMBER:** BWO-6098-18(001) 501427

**DATE:** 1-31-05 (Revised 3-21-05)

**DESCRIPTION A:** This Work shall consist of all site Work and all construction Work necessary in constructing the District Headquarters Building at Hattiesburg, Forrest County, Mississippi in accordance with these Specifications and conforming with the Drawings.

It is the intention of these Specifications to provide the necessary items and instruction for a complete building including all code compliance. Omission of items or instruction necessary or considered standard good practice for the proper installation and construction of the building shall not relieve the Contractor of furnishing and installing such items and conforming to the building codes having jurisdiction.

### GENERAL INDEX

DOCUMENT 00010	TABLE OF CONTENTS
DOCUMENT 00015	INDEX OF DRAWINGS
DOCUMENT 00100	ADVERTISEMENT FOR BIDS
DOCUMENT 00150	PRE-BID MEETING
DOCUMENT 00200	INSTRUCTIONS TO BIDDERS
DOCUMENT 00300	NOTICE TO BIDDERS
DOCUMENT 00320	GEOTECHNICAL DATA (WITH REPORT FOLLOWING)
DOCUMENT 00400	PROPOSAL FORM
DOCUMENT 00500	AGREEMENT FORM
DOCUMENT 00600	CONTRACT BOND
DOCUMENT 00602-1	NON-COLLUSION CERTIFICATION
DOCUMENT 00602-2	NON-COLLUSION CERTIFICATION
DOCUMENT 00604	STATE BOARD OF CONTRACTORS REQUIREMENTS
DOCUMENT 00605	HAUL PERMIT FOR BRIDGES WITH POSTED LIMITS
DOCUMENT 00700	GENERAL CONDITIONS (WITH AIA 201 FOLLOWING)
DOCUMENT 00800	SUPPLEMENTARY CONDITIONS
DOCUMENT 00910	ADDENDUM NUMBER 1

### DIVISION 1 GENERAL REQUIREMENTS

SECTION 01110	SUMMARY OF WORK
SECTION 01210	ALLOWANCES
SECTION 01290	PAYMENT PROCEDURES
SECTION 01295	SCHEDULE OF VALUES
SECTION 01298	CHANGE ORDER PROCEDURES
SECTION 01310	PROJECT MANAGEMENT AND COORDINATION
SECTION 01315	PROJECT MEETINGS
SECTION 01320	CONSTRUCTION PROGRESS DOCUMENTATION
SECTION 01330	SUBMITTAL PROCEDURES
SECTION 01425	REFERENCE DOCUMENTS
SECTION 01455	TESTING LABORATORY SERVICES

SECTION	01500	TEMPORARY FACILITIES AND CONTROLS
SECTION	01610	BASIC PRODUCT REQUIREMENTS
SECTION	01630	PRODUCT OPTIONS AND SUBSTITUTION PROCEDURES
SECTION	01735	CUTTING AND PATCHING
SECTION	01740	CLEANING
SECTION	01770	CLOSEOUT PROCEDURES
SECTION	01785	PROJECT RECORD DOCUMENTS
<b>DIVISION 2</b>	<b>SITE CONSTRUCTION</b>	
SECTION	02055	SOIL MATERIALS
SECTION	02220	SITE DEMOLITION
SECTION	02225	BUILDING DEMOLITION
SECTION	02230	SITE CLEARING
SECTION	02300	SITE EARTHWORK
SECTION	02316	BUILDING EARTHWORK
SECTION	02351	DRILLED CAISSONS
SECTION	02365	SOIL TREATMENT FOR TERMITE CONTROL
SECTION	02630	STORM AND SUBSURFACE DRAINAGE
SECTION	02775	CONCRETE SIDEWALKS
SECTION	02920	GRASSING
<b>DIVISION 3</b>	<b>CONCRETE</b>	
SECTION	03100	CONCRETE FORMS AND ACCESSORIES
SECTION	03200	CONCRETE REINFORCEMENT
SECTION	03300	CAST-IN-PLACE CONCRETE
<b>DIVISION 4</b>	<b>MASONRY</b>	
SECTION	04200	MASONRY UNITS
<b>DIVISION 5</b>	<b>METALS</b>	
SECTION	05120	STRUCTURAL STEEL
SECTION	05210	STEEL JOISTS
SECTION	05311	STEEL DECK
SECTION	05400	COLD-FORMED METAL FRAMING
SECTION	05401	LIGHT GAUGE STEEL PRE-ENGINEERED / MANUF. TRUSSES
SECTION	05500	METAL FABRICATION
SECTION	05720	ARCHITECTURAL ORNAMENTAL HANDRAIL AND RAILING
SECTION	05730	ORNAMENTAL METALS
<b>DIVISION 6</b>	<b>WOOD AND PLASTICS</b>	
SECTION	06100	ROUGH CARPENTRY
SECTION	06400	ARCHITECTURAL WOODWORK
<b>DIVISION 7</b>	<b>THERMAL AND MOISTURE PROTECTION</b>	
SECTION	07210	BUILDING INSULATION
SECTION	07218	SPRAY-ON INSULATION SYSTEM
SECTION	07220	SLOPED ROOF DECK INSULATION
SECTION	07260	VAPOR RETARDERS
SECTION	07412	ALUMINUM COMPOSITE PANEL SYSTEM
SECTION	07545	THERMOPLASTIC MEMBRANE ROOFING
SECTION	07600	FLASHING AND SHEET METAL
SECTION	07610	SHEET METAL ROOFING
SECTION	07650	FLEXIBLE FLASHING
SECTION	07700	ROOF SPECIALTIES AND ACCESSORIES
SECTION	07840	FIRESTOPPING
SECTION	07920	JOINT SEALANTS

**DIVISION 8 DOORS AND WINDOWS**

SECTION	08100	METAL DOORS AND FRAMES
SECTION	08210	WOOD DOORS
SECTION	08710	DOOR HARDWARE
SECTION	08800	GLAZING
SECTION	08916	ALUMINUM CURTAINWALL AND ENTRANCES

**DIVISION 9 FINISHES**

SECTION	09050	COLOR DESIGN
SECTION	09125	SUSPENDED GYPSUM BOARD SYSTEM
SECTION	09250	GYPSUM BOARD
SECTION	09310	CERAMIC TILE
SECTION	09340	PAVER TILE
SECTION	09400	TERRAZZO
SECTION	09510	ACOUSTICAL CEILINGS
SECTION	09549	WIDE PANEL METAL CEILINGS
SECTION	09640	WOOD FLOORING
SECTION	09650	RESILIENT FLOORING
SECTION	09655	RUBBER FLOORING
SECTION	09680	CARPET
SECTION	09725	VINYL WALL COVERING
SECTION	09728	FABRIC WALL COVERING
SECTION	09900	PAINTS AND COATINGS

**DIVISION 10 SPECIALTIES**

SECTION	10100	VISUAL DISPLAY BOARDS
SECTION	10165	PLASTIC LAMINATE TOILET COMPARTMENTS
SECTION	10200	LOUVERS AND VENTS
SECTION	10245	ARCHITECTURAL SCREEN WALL
SECTION	10260	WALL AND CORNER GUARDS
SECTION	10400	IDENTIFICATION DEVICES
SECTION	10420	PLAQUES
SECTION	10525	FIRE EXTINGUISHERS
SECTION	10526	DEFIBRILLATORS
SECTION	10534	TRANSLUCENT CANOPIES AND WALKWAY COVERS
SECTION	10670	STORAGE SHELVING
SECTION	10810	TOILET ACCESSORIES
SECTION	10900	WARDROBE AND CLOSET SPECIALTIES

**DIVISION 11 EQUIPMENT**

SECTION	11455	RESIDENTIAL APPLIANCES & EQUIPMENT
---------	-------	------------------------------------

**DIVISION 12 FURNISHINGS**

SECTION	12492	HORIZONTAL LOUVER BLINDS
---------	-------	--------------------------

**DIVISION 13 SPECIAL CONSTRUCTION (Not Used)**

**DIVISION 14 CONVEYING SYSTEMS**

SECTION	14245	HYDRAULIC PASSENGER ELEVATOR
---------	-------	------------------------------

**DIVISION 15 MECHANICAL**

SECTION	15010	MECHANICAL GENERAL PROVISIONS
SECTION	15011	SCHEDULE OF SUBMITTAL DATA
SECTION	15015	DESIGN CONDITIONS
SECTION	15016	CODES AND REGULATIONS
SECTION	15020	IDENTIFICATION OF PIPING SYSTEMS
SECTION	15025	MOTOR CONTROLS AND WIRING
SECTION	15030	TRENCH EXCAVATION AND BACKFILL
SECTION	15080	HVAC TEST AND BALANCE
SECTION	15100	MECHANICAL SUPPORTING SYSTEMS
SECTION	15180	MECHANICAL SYSTEMS INSULATION
SECTION	15200	VIBRATION ISOLATORS
SECTION	15317	REFRIGERANT PIPING SYSTEMS
SECTION	15400	PLUMBING BASIC MATERIALS AND METHODS
SECTION	15431	DRAINS, CLEANOUTS & DRAINAGE ACCESSORIES
SECTION	15442	WATER HEATERS - ELECTRIC
SECTION	15450	PLUMBING FIXTURES AND TRIM
SECTION	15501	FIRE PROTECTION
SECTION	15605	ELECTRIC WALL HEATERS
SECTION	15670	AIR COOLED CONDENSING UNITS (CU-1, CU-2, AND CU-3)
SECTION	15680	AIR COOLED CONDENSING UNIT (CU-5)
SECTION	15733	PACKAGED ROOFTOP AIR CONDITIONING UNITS
SECTION	15740	VARIABLE AIR VOLUME BOXES
SECTION	15840	DUCTWORK AND ACCESSORIES
SECTION	15841	FILTERS
SECTION	15850	FANS
SECTION	15860	CENTRAL AIR HANDLING UNITS
SECTION	15870	GRILLES, REGISTERS AND DIFFUSERS
SECTION	15910	BUILDING AUTOMATION SYSTEM
SECTION	15920	CHANGEOVER / BYPASS VARIABLE AIR VOLUME SYSTEM CONTROLLER

**DIVISION 16 ELECTRICAL**

SECTION	16010	ELECTRICAL GENERAL REQUIREMENTS
SECTION	16100	BASIC MATERIALS AND METHODS
SECTION	16115	CABLE TRAYS
SECTION	16200	SERVICE AND DISTRIBUTION
SECTION	16300	LIGHTING
SECTION	16420	EMERGENCY ELECTRICAL GENERATING SYSTEM
SECTION	16430	AUTOMATIC LOAD TRANSFER SWITCH
SECTION	16552	LIGHTED DISPLAY SHELVING AND ACCESSORIES
SECTION	16640	SECURITY SYSTEMS
SECTION	16660	CLOSED CIRCUIT TELEVISION SYSTEM
SECTION	16721	FIRE ALARM AND DETECTION SYSTEM
SECTION	16920	MOTOR CONTROLS AND WIRING

\*\*\* END OF DOCUMENT\*\*\*

SECTION 01290

PAYMENT PROCEDURES  
(Revised 3-21-05)

PART 1 GENERAL

1.01 METHOD OF MEASUREMENT: The method of measurement and payment shall conform to the applicable provisions of Article 9 of the AIA Document A201-1997 General Conditions of the Contract for Construction.

1.02 APPLICATION FOR PAYMENT

A. Format:

1. Applications for Payments will be prepared on AIA forms G702-Application and Certificate for payment and G703-Continuation Sheet; or, a computer generated form containing similar data may be used.

B. Preparation of Application:

1. Present required information in type written form.
2. Execute certification by signature of authorized officer.
3. Use data from approved Schedule of Values. Provide dollar value in each column for each line item for portion of Work performed and for stored products.
4. List each authorized Change Order (Supplemental Agreement) as an extension on continuation sheet, listing Change Order (Supplemental Agreement) number and dollar amount as for an original Item of Work.
5. Prepare Application for Final Payment as specified in Section 01770-Closeout Procedures.

C. Submittal Procedures:

1. Submit 5 copies of each Application for Payment to the Project Engineer.
2. Submit an updated construction schedule with each Application for Payment as described in Section 01320-Construction Progress Documentation.
3. Submit request for payment at intervals agreed upon by the Project Engineer, Owner, and Contractor.
4. Submit requests to the Project Engineer at agreed upon times, or as may be directed otherwise.

D. Substantiating Data:

1. Submit data justifying dollar amounts in question when such information is needed.
2. Provide one copy of the data with a cover letter for each submittal.
3. Indicate the Application number, date and line item number and description.

1.03 STATEMENTS AND PAYROLLS

- A. The submission by the Contractor of the actual weekly payrolls showing all employees, hours worked, hourly rates, overtime hours, etc., or copies thereof, is not required to be turned in. However, each Contractor and Subcontractor shall preserve weekly payroll records for a period of three years from the date of Contract completion. All Contractor personnel working at the project site will be paid unconditionally and not less often than once a week without subsequent deduction or rebate on any account, except such payroll deductions as are permitted by regulations, the full amounts of wages and bona fide fringe benefits due at time of payment.

- B. The payroll records shall contain the name, address, social security number, classification, rate of pay, daily and weekly number of hours worked, itemized deductions and actual wages paid to each employee.
- C. Upon request, the Contractor will make payroll records available at the project site for inspection by the Department Compliance Officer or authorized representative and will permit such officer or representative to interview employees on the job during working hours.
- D. The Contractor and Subcontractors shall submit Form CAD-880, "Weekly Summary of Wage Rates", each week to the Project Engineer. The forms may be obtained from the Contract Compliance Officer, Contract Administration Division, Mississippi Department of Transportation, Jackson, Mississippi. Custom forms, approved by Contract Administration Division, may be used in lieu of CAD forms.

1.04 BASIS OF PAYMENT

- A. This Work will be paid for by Contract Sum for the construction of the District Headquarters Building at Hattiesburg in District Six, Forrest County, Mississippi. The Contract Sum shall be full compensation for all site work, for furnishing all materials, and all other Work and effort of whatever nature in the construction of the building, installation of underground and other equipment, and final clean-up of the area. It shall also be complete compensation for all equipment, tools, labor, and incidentals necessary to complete the Work.
- B. Payment will be made under:

MDOT Project No. BWO-6098-18(001) 501427

lump sum

**TOTAL PROJECT CONTRACT SUM**

**LUMP SUM**

PART 2 PRODUCTS  
Not Used

PART 3 EXECUTION  
Not Used

\*\*\*END OF SECTION\*\*\*

SECTION 02365

SOIL TREATMENT FOR TERMITE CONTROL

(Revised 3-21-05)

PART 1 GENERAL

- 1.01 SECTION INCLUDES: Soil treatment for termite control.
- 1.02 SUBMITTALS
- A. Submit manufacturer's technical product data and application instructions prior to application for Project Engineer's approval.
  - B. Submit sample copies of the Termite Soil Treatment Guarantee form prior to application for Project Engineer's approval.
  - C. Quality Assurance/Control Submittals: Submit identification of at least 3 projects of similar scope along with name, address, and telephone number of the Architect, Owner and General Contractor.
- 1.03 QUALITY ASSURANCE: In addition to the requirements of these Specifications, comply with manufacturer's instructions and recommendations for the Work, including preparation of substrate and application.
- A. Engage a professional pest control operator, licensed by the State of Mississippi, Mississippi Department of Agriculture and Commerce, Bureau of Plant Industry, and in accordance with regulations of governing authorities for application of soil treatment solution. The pest control operator is to have the aforementioned valid license, the company technician is to have a valid identification card for pest control, and the company vehicle is to be clearly marked with the company name.
  - B. The professional pest control operator specializing in Soil Treatment for Termite Control, with 5 years minimum experience, who has completed work similar to that indicated for this project and with a record of successful in-service performance.
  - C. Comply with Mississippi Regulations Governing Pest Control Operators in following the labels of the termiticide.
- 1.04 PROJECT CONDITIONS
- A. Do not apply soil treatment solution until excavating, filling and grading operations are completed, except as otherwise required in construction operations.
  - B. To insure penetration, do not apply soil treatment to frozen or excessively wet soils or during inclement weather. Comply with other handling and application instructions of the soil toxicant manufacturer.
  - C. Remove all non-pressure treated wood contacting soil. Remove grade stakes prior to applying horizontal barrier and all form boards, stakes and concrete over pour prior to applying vertical soil treatment.
- 1.05 GUARANTEE: Furnish 2 copies of written guarantee certifying that the applied soil poisoning treatment will prevent the infestation of subterranean termites and, that termite contractor will re-treat the soil and also repair or replace any damage caused by termite infestation without expense to the Owner. Provide guarantee for a period of 5 years from the date of treatment, signed by the Applicator and the Contractor.

## PART 2 PRODUCTS

### 2.01 SOIL TREATMENT SOLUTION

- A. Use an emulsible concentrate insecticide for dilution with water specially formulated to prevent infestation by termites as recommended by the Southern Forest Experiment Station, Forest Insect Laboratory at Gulfport, Mississippi, and registered by the Bureau of Plant Industry for use in structural pest control work. Fuel oil will not be permitted as a diluent. Provide a working solution of one of the following chemical elements:
  - 1. Horizontal barrier: Cypermethrin, Prevail or Talstar.
  - 2. Vertical barrier: Fipronil.
- B. Other solutions may be used as recommended by Applicator and if acceptable to local and state governing authorities. Use only soil treatment solutions that are not injurious to plants.

## PART 3 EXECUTION

- 3.01 INSPECTION: Applicator must examine the areas and conditions under which soil treatment for termite control is to be installed and notify the Contractor in writing of conditions detrimental to the proper and timely completion of the Work. Do not proceed with the Work until unsatisfactory conditions have been corrected in a manner acceptable to the Applicator.
- 3.02 APPLICATION: Remove foreign matter, which could decrease effectiveness of treatment on areas to be treated. Loosen, rake, and level soil to be treated, except previously compacted areas under slabs and foundations. Toxicants may be applied before placement of compacted fill under slabs, if recommended by toxicant manufacturer.
  - A. Application Rates: Under slab-on-grade, suspended slab, foundation footings and other similar structures, treat the soil before concrete slabs are poured using either power sprayer or tank-type garden sprayer. Apply soil treatment solution, using color dye marking agent to insure the area is treated, as follows:
    - 1. Termiticide applied for the prevention of termites shall comply with the manufacturer's label and shall not be applied at concentrations or volumes less than specified on the label.
    - 2. Reapply soil treatment solution to areas disturbed by subsequent excavation or other construction activities following application.
  - C. Allow a minimum of 12 hours for drying after application, before beginning concrete placement or other construction activities.
- 3.03 PROTECTION: Prior to each application, the applicator shall notify the Contractor of the intended application and instruct the responsible person to notify construction workers and other site individuals to leave the treated area and not to return until chemical has been installed into the soil.
  - A. Post signs in the areas of application warning workers that soil poisoning has been applied. Remove signs when areas are covered by other construction.

\*\*\*END OF SECTION\*\*\*

SECTION 07218

SPRAY-ON INSULATION SYSTEM  
(Added 3-21-05)

PART 1 GENERAL

1.01 SECTION INCLUDES

- A. The products of the Work and the requirements for their quality, delivery, handling, storage, protection and installation.
- B. Sprayed cellulose thermal insulation of under-slab deck/structure in building crawl space.

1.02 RELATED ITEMS

- A. Clips, hangers, supports, sleeves and other attachments to spray bases are to be placed by other trades prior to the application of sprayed insulation.
- B. Ducts, piping conduit or other suspended equipment shall not be positioned until after the application of sprayed insulation.

1.03 SUBMITTALS

- A. Product Data: Submit manufacturer's technical data, installation instructions, and manufacturer's certificate that the product meets or exceeds the specified requirements.
- B. Quality Assurance/Control Submittals: Submit manufacturer's written certification that product contains no asbestos, fiberglass or other man made mineral fiber and copy of manufacturer's ISO 9001: 2000 Certification

1.04 QUALITY ASSURANCE

- A. Manufacturer: Shall be ISO 9001: 2000 Certified and subscribe to independent laboratory follow-up inspection services of Underwriters Laboratories or Factory Mutual. Each bag shall be labeled accordingly.
- B. Applicator: Shall be licensed by the manufacturer.

1.05 DELIVERY, STORAGE and HANDLING:

- A. Deliver in original, unopened containers bearing the name of the manufacturer, product identification and references to U.L. testing.
- B. Store materials dry, off the ground and under cover.
- C. Protect liquid adhesive from freezing.

PART 2 PRODUCTS

2.01 ACCEPTABLE MANUFACTURERS:

- A. Specifications are based on products manufactured by International Cellulose Corporation, 12315 Robin Boulevard, Houston, TX 77045, Phone: (713) 433-6701 or (800) 444-1252 Fax: (713) 433-2029. Contact International Cellulose Corporation for approved applicators.
- B. Equivalent products by the following manufacturers are acceptable:
  - 1. Nu-Wool Insulation Co., Inc., 2472 Port Sheldon Street, Jenison, MI 49428, Tel: (616) 669-2700.
  - 2. ThermoCon, Inc., 2500 Jackson Street, Monroe, LA 71202, Tel: (800) 854-1907.

- C. Substitutions shall fully comply with specified requirements and Section 01630 – Product Options and Substitution Procedures.

## 2.02 MATERIALS

### A. K-13 Spray-On-Systems

1. Color shall be “Tan”.
2. Apply at minimum thickness to provide an R-value of 20.
3. Comply with ASTM E-736 for field-tested bond strength; tested @ > 5 years.
  - a. Not less than 400 psf.
  - b. Not less than 600 times its weight @ 1”.
4. Comply with ASTM E-84/U.L. 723, Tested at minimum of 5” thickness Class 1, Class A Flame Spread 5, Smoke Development 5
5. Comply with ASTM E-1042.
6. Non corrosive per ASTM C-739.
7. Bond Deflection per ASTM E-759: 6” deflection in 10’ span - No spalling or delaminating.
8. Cohesive Strength at time of application per Method WS-2000: > 700 Grams.

## PART 3 EXECUTION

### 3.01 EXAMINATION

- A. Examine surfaces and report unsatisfactory conditions in writing. Do not proceed until unsatisfactory conditions are corrected.

### 3.02 PREPARATION

- A. Provide masking, drop cloths or other satisfactory coverings for materials/surfaces that are not to receive insulation to protect from over-spray.
- B. Coordinate installation of sprayed cellulose fiber with work of the other trades.
- C. Prime surfaces as required by the manufacturers’ instructions or as determined by examination.

### 3.03 INSTALLATION

- A. Thickness will be determined as the minimum thickness measured as per ASTM E-605 field test procedure.
- B. Install spray applied insulation according to manufacturer’s recommendations.
- C. Cure insulation with continuous natural or mechanical ventilation.
- D. Remove and dispose of over-spray and all debris caused by the application.

### 3.04 PROTECTION

- A. Protect finished installation until properly cured and inspected by the Project Engineer.

\*\*\*END OF SECTION\*\*\*

SECTION 12492

HORIZONTAL LOUVER BLINDS

(Revised 3-21-05)

PART 1 GENERAL

- 1.01 SECTION INCLUDES: 2" horizontal louver blinds, accessories, attaching hardware, labor and equipment necessary to complete satisfactory installation.
- 1.02 RELATED SECTIONS: Section 09050 - Color Design
- 1.03 SUBMITTALS
- A. Submit manufacturer's descriptive literature indication materials, finishes, construction and installation instructions, and data verifying that product meets requirements specified. Include manufacturer's recommendations for maintenance and cleaning.
  - B. Shop Drawings: Indicate field-measured dimensions of openings to receive blinds. Include illustrations of special accessory components not included in manufacturer's product data. Indicate details of head and sill conditions, corner conditions, and conditions between adjacent blind units.
  - C. Color Samples: Submit two 6" (0.15m) samples of material indicating full color range and color variation.
  - D. Product Sample: Submit one 16" wide by 24" long fully functional sample blind.
- 1.04 QUALITY ASSURANCE: Manufacturer and installer shall have at least five years experience in this type of product and installation.
- 1.05 WARRANTY: Provide manufacturer's standard five year written warranty against defects in materials and workmanship beginning at date of substantial completion.
- 1.06 PRODUCT DELIVERY: Blinds shall be carefully handled and stored to prevent damage to materials, finishes and operating mechanisms.

PART 2 PRODUCTS

2.01 ACCEPTABLE MANUFACTURERS

- A. Drawings and specifications are based on products manufactured by Skandia Window Fashions, 270 Crossway Road, Tallahassee, FL 32305; Tel. (800) 874-3168.
- B. Equivalent products by the following manufacturers are acceptable:
  - 1. Levolor Home Fashions Contract Division, 4110 Premier Dr., High Point, NC 27265. Tel. (336) 812-8181.
  - 2. Hunter Douglas, Inc., 2 Park Way, Upper Saddle River, NJ 07458. Tel. (800) 727-8953.
  - 3. Springs Window Fashions Division, Inc., P.O. Box 500, Montgomery, PA 17752. Tel. (570) 547-6671.
- C. Substitutions shall fully comply with specified requirements and Section 01630 – Product Options and Substitution Procedures.

2.02 MATERIALS

- A. Provide faux wood blinds equal to Inspire® 2" Traditional Faux Wood Blinds by Skandia Window Fashions.

## 2.03 COMPONENTS

- A. Valance: Provide standard valance, 2 5/8" high, molded. Finish to match slats.
- B. Head Channel Hardware: Metal hardware shall be electroplated with lift cords cloth tape guided by acetal low friction thermoplastic grommets in the head channel that prevent wear and discoloration. Operating hardware shall be mechanically locked into head channel by means of snap-in fittings with no mechanical cleats visible from underside of headrail.
- C. Bottomrail: Rectangular molded, 5/8" high by 2" deep. Bottomrail finished shall match slat color and finish.
- D. Slats: Slats shall be made from lead-free, UV-stabilized, integrally colored, opaque, extruded PVC and are resistant to warping, will not crack or yellow, antistatic, and dust-repellent treated. Slats shall be nominally 2" wide, by 1/8" thick. Spacing shall be manufacturer's standard.
- E. Tilt Control: Enclosed worm-gear mechanism and linkage rod for the following operation:
  - 1. Tilt Operation: Manual with wand.
  - 2. Length of Tilt Control: Length required to make operation convenient from floor level and reachable over adjacent built in shelves and desktops.
  - 3. Tilt: Full tilt.
- F. Ladder: Braided string, evenly spaced to prevent long term slat sag.
- G. Cord Lock: Metal cord lock shall be of a snap-in design and incorporate a floating shaft-type locking pin. The freely rotating locking pin shall offer minimum wear to cord. Cord lock shall incorporate a crash-proof safety feature that shall lock blind automatically upon release of cord. Locks pull cord to stop blind in any position in ascending or descending travel.
- H. Lift Cord: Lift cord shall be braided with polyester jacket and center core or an approved equal construction. Size of cord shall be 1.8mm. Cords shall be detachable, if required, and shall be of sufficient length to properly control the raising or lowering of the blind. Lift cords shall be equipped with tassels to match slat finish. Cord ends shall be securely anchored to the bottomrail and it shall be possible to detach and attach cords.
- I. Blinds shall be made with the following cord lock and tilter locations when viewed from within the room:
  - 1. Installation shall have tilter at left, cord lock at right (standard).
  - 2. Where blinds are located at sidelights of doors, tilter and cord lock shall be located on the same side and on the far side away from the door.
- J. End Support Brackets: Universal hinged cover and support brackets of phosphate treated steel with a prime coat of vinyl primer and a finish coat of baked on polyester enamel in color to match headrail. Brackets shall facilitate easy removal of head channel and will include an adjustable tab to eliminate lateral headrail movement.
- K. Intermediate Support Brackets: Brackets shall be furnished for blinds over 36" wide. Maximum spacing for intermediate support brackets shall be 36".

- L. End Stiffeners: Thermoplastic end stiffener caps shall be inserted at each end of the headrail.
  - M. The blind shall be free of sharp edges, burrs or other defects which might be harmful. When other materials result in improved specifications, they shall be adopted.
  - N. Color: Color of headrail, bottomrail, ladder, wand, cord and accessories shall coordinate with slats. Plastic headrail components shall be white.
- 2.04 FABRICATION
- A. Prior to fabrication, verify actual opening dimensions by on-site measurement. Calculate blind dimensions to fit with specified tolerances.
  - B. Fabricate blinds to fill openings from head to sill and jamb to jamb. One headrail per window - may have up to two blinds per headrail if window width exceeds blind maximum. Blind divisions shall be located at mullions.
  - C. Fabricate blinds to fill all exterior openings, unless noted otherwise. Do not install blinds at Vestibule 102, Vestibule 103, Stair 117, Stair 139, Lobby 151, Lobby 201, Stair 207, or Stair 240. Provide blinds at Lobby 101 only at window area under gypsum board soffit at east and west ends of the space (blind to mount at horizontal mullion behind soffit). Provide blinds at interior windows at Law Enforcement 133, Fiscal Administrator 205, and mount on door 154C in Auditorium 154. At windows N, O, and P in Auditorium 154, provide two blinds per window (bottom blind to be mounted at center-most horizontal mullion).

### PART 3 EXECUTION

- 3.01 INSPECTION AND PREPARATION: Blind installer shall be responsible for inspection of site, installation conditions, and field measurements prior to blind installation.
- 3.02 INSTALLATION
- A. Install blinds in accordance with manufacturer's procedures except as otherwise specified herein.
  - B. Install intermediate support brackets and extension brackets as needed to prevent deflection in headrail.
  - C. Install blinds with adequate clearance to permit smooth operation of blinds and any sash operators.
  - D. Set tilt and lift controls. Demonstrate blinds to be in smooth, uniform working order.
  - E. Blinds may be dusted. Gently clean soiled blind surfaces with a mild soap solution. Do not use steam, hot water, bleach or any abrasive or solvent based cleaners.

\*\*\*END OF SECTION\*\*\*