SECTION 905 -- PROPOSAL (CONTINUED)

I (We) hereby certify by digital signature and electronic submission via Bid Express of the Section 905 proposal below, that all certifications, disclosures and affidavits incorporated herein are deemed to be duly executed in the aggregate, fully enforceable and binding upon delivery of the bid proposal. I (We) further acknowledge that this certification shall not extend to the bid bond or alternate security which must be separately executed for the benefit of the Commission. This signature does not cure deficiencies in any required certifications, disclosures and/or affidavits. I (We) also acknowledge the right of the Commission to require full and final execution on any certification, disclosure or affidavit contained in the proposal at the Commission's election upon award. Failure to so execute at the Commission's request within the time allowed in the Standard Specifications for execution of all contract documents will result in forfeiture of the bid bond or alternate security.

Bidder acknowledges receipt of and has added to and made a part of the proposal and contract documents the following addendum (addenda): ADDENDUM NO. 2/21/2018 DATED ADDENDUM NO. DATED ADDENDUM NO DATED ADDENDUM NO. DATED ADDENDUM NO. DATED ADDENDUM NO DATED Number Description TOTAL ADDENDA: (Must agree with total addenda issued prior to opening of bids) Revised Table of Contents; Added Supplement to NTB 401; Amendment EBS Download Required. Respectfully Submitted, DATE Contractor Signature TITLE **ADDRESS** CITY, STATE, ZIP FAX ___ E-MAIL (To be filled in if a corporation) Our corporation is chartered under the Laws of the State of and the names, titles and business addresses of the executives are as follows: President Address Secretary Address Treasurer Address

The following is my (our) itemized proposal.

HSIP-0231-00(082)/ 107251301000 & HSIP-0231-00(082)/ 107251302000

George & Jackson County(ies)

Revised 01/26/2016

MISSISSIPPI DEPARTMENT OF TRANSPORTATION TABLE OF CONTENTS

PROJECT: HSIP-0231-00(082)/107251301 - George HSIP-0231-00(082)/107251302 - Jackson

Section 901 - Advertisement

Section 904 - Notice to	o Bidders
#1	Governing Specification
#2	Status of ROW, w/ Attachments
#7	Disadvantaged Business Enterprise In Federal-Aid Highway Construction, w/ Supplement
#8	Errata and Modifications to the 2017 Standard Specifications
#9	Federal Bridge Formula
#10	DUNS Requirement for Federal Funded Projects
#12	MASH Compliant Devices
#113	Tack Coat
#296	Reduced Speed Limit Signs
#401	Standard Drawings w/Supplement
#445	Mississippi Agent and Qualified Nonresident Agent
#571	Contract Time
#572	Specialty Items
#573	Scope of Work

Required Federal Contract Provisions -- FHWA 1273, w/Supplements

Section 907 - Special Provisions

906

907-102-2	Bidding Requirements and Conditions
907-103-2	Award and Execution of Contract
907-416-2	High Friction Surface Treatment
907-618-3	Additional Signing Requirements, w/Supplement
907-626-6	Audible Thermoplastic Traffic Markings
907-630-3	LED Enhanced Traffic Sign

Section 905 - Proposal, Proposal Bid Items, Combination Bid Proposal

Certification of Performance - Prior Federal-Aid Contracts

Certification Regarding Non-Collusion, Debarment and Suspension

SAM.GOV Registration and DUNS Number

Section 902 - Contract Form

Section 903 - Contract Bond Forms

Form -- OCR-485

(REVISIONS TO THE ABOVE WILL BE INDICATED ON THE SECOND SHEET OF SECTION 905 AS ADDENDA)
02/21/2018 09:48 AM

MISSISSIPPI DEPARTMENT OF TRANSPORTATION

SUPPLEMENT TO NOTICE TO BIDDERS NO. 401

DATE: 02/21/2018

PROJECT: HSIP-0231-00(082) / 107251301 & 302 – George and Jackson Counties

After the last drawing on page 25, add the following.

2 Supplement to Notice To Bidders No.401- Cont'd.

												2	Supplement to Notice To Bidders No.401- C
STATE PROJECT NO. MISS.	M1-6	0.080*	# 11/2 Cd* x 24°) = 11 Cd* x 24°) = 148 (38° x 24°)	12" SERIES "D" (SEE NOTE BELOW)	BLACK OUTSIDE BORDER 24" X 24" (1 OR 2 DIGITS)	30° X 24° (3 DIGITS) BLACK WHITE	BACKGROUND	1	(VERT. PUNCHING) (HORIZ. PUNCHING)	VEKT, CENTER VERT, CENTER	M6-3	080.0	
	M1-4	0.080°	S	SEE NOTES 1 & 2 BELOW)	BLACK OUTSIDE BORDER 24" X 24" (I OR 2 DIGITS)	X 24* (3 BLACK WHITE	BACKGROUND	1	2 HORIZ, PUNCI 12* FRON	Z. 21	L M6-2L	0.080*	N 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	M1=1	0.100*		(SE	¾₁ WHITE 36" X 36" (1 OR 2 DIGITS)	WHITE BOTTOM-BILE	ALL		5° FROM		M6-1LA M6-1R M6-1RA	0.080	10/2
	M1=1	0.080°		(SEE NOTES 1 & 2 BELOW)	1/2* WH]	24" (3 DIGITS)	А		2		M5-2RA M6-1L		
	D10-4 D10-5	0.100*	WEST WEST WIEST WILE ALL CENTRAL STREET OF SERVICE OF S	6" SERIES "B" 8" SERIES "B"	1/2" WHITE 1/2" WHITE	THM 307	ALL ALL	-	_	6": 48" 6": 54"	M5-2LA	0.080*	# WHITE BLA MASTA
	010=3a D	0.100*	2.2	4" SERIES "B" 6" SERI 10" SERIES "D" 8"	1/2" WHITE 1/2"		ALL	1	2	67:547	AS-1RA	.080.	## ## ## ## ## ## ## ## ## ## ## ## ##
	D18-1a D18-2a	0.080" 0.100"	.2/,7	-B- 4" SERIES "B" 5 "D" 10" SERIES "D"	HITE 1/2" WHITE			-		EE	M5-11	0.0	2. SE BLAILE B. SE WHITE B. SE WHITE B. SE WHITE B. SE WHITE B. SE
	D10-3 D1	0.100" 0.0	1/2,	4" SERIES "B" 4" SERIES "B" 10" SERIES "D"	//2" WHITE //2" WHITE		ALL ALL	1	2 2	6°: 42" 3°: 33°	M2=5	0.080	
	2-Ø10	0.080*	.2	4" SERIES "B" 10" SERIES "D"	1/2" WHITE	WHITE ORPEN	ALL	-	2	7 33-	* VEØ1-EM * VE-EM	4	SPUT SERIES 'C' SERIES 'C' SERIES 'C' SERIES 'C' SERIES 'C' WHITE BLUE ALL I I I I I I I I I I I I I I I I I I
	09-2 018-1	0.080" 0.080"		20" SERIES 30" SERIES 4" SERIES "B" "E MOD." E MOD." 10" SERIES "D"	TTE 74" WHITE 1/2" WHITE	WHITE	ALL ALL	1 1	2 18" (VERT.	_	M2-1A M3-3*	0.080*	SOL
	SIGN NUMBER	ALUMINUM (6Ø61-T6) SIGN BLANK THICKNESS	LEGENO R = 1/2*		WIDTH OF BORDER OUTSIDE 1/2" WHITE		REFLECTORIZATION ALL	OF POSTS	NUMBER OF HOLES TO BE 2 PUNCHED (3%" DIA.) PUNCHING DISTANCE FROM 12" (VERT	1.1	ı.	261-T6) FHICKNESS	LECEND LECEND

3 Supplement to Notice To Bidders No.401- Cont'd.

													3	3 Supp	oler	nen	t t	o 2	No	otio	ce	T	o	Bio	dders			
PROJECT NO.	R4-3	0.125*	SLOWER TRAFFIC KEEP RIGHT	R=3*	1/4" BLACK 3/4" WHITE	48" X 60"	WHITE	BACKGROUND 1	9	9,	4*; 30"; 56"		0.125*			R=3" ES "C"	1/4" BLACK ¾" WHITE	48" X 60"	BLACK WHITE	BACKGROUND	_	9	r.	47; 307; 567	PORTATION		WORKING NUMBER SN-3A	sнет NUMBER 6304
STATE MISS.	- E	0.100"	SL(TR X RI	R=2//4*		36" × 48"	WHITE	BACKGROUND 1	4	3*	9', 39'	R11-1		KEEP	MEDIAN	R=3'		4						,4	T OF TRANS	GNS		17
	R3-5	0.080°	ONIT	R=1%.	% BLACK //s WHITE	30" X 36"	WHITE	BACKGROUND 1	2	15" (VERT, CENTER)	6"; 30"		0.125			R=2//4" 8" SERIES "C"	TE %" BLACK			BAC		4 2		9, 39,	MISSISSIPPI DEPARTMENT OF TRANSPORTATION ROADWAY DESIGN DIVISION STANDARD PLAN	STANDARD ROADSIDE SIGNS		ISSUE DATE: MAY 01, 2017
	4	0.100"		R=21/4°	78" BLACK 5%" WHITE	36" x 36"	WHITE BACKGROUND.	CIRCLE, & DIAG.	2	18" (VERT. CENTER)	6"; 30"	R8-4	0.100*	EMERGENCY PARKING	ONLY	6" SERIES "D"	% BLACK % WHITE	48" X 36"	BLACK	BACKGROUND	7	4 9		3*; 33*	WISS	NOISIA:	38	3TAG ISSUE
	R3-4	0.080*		R=1/2°	% BLACK % WHITE	24"		CIRCLE, & DIAG.	2	12" (VERT. CENTER)	3"; 21"		0.080°	EMEI	_	4" SERIES "D"	%" BLACK %" WHITE	30" × 24"	BLACK	BACKGROUND	-	Z annu oriente	IST (VERT), CENTERJ	3*; 21*			ļ	
	R3-2	0.100*		R=2/4*	% BLACK % WHITE	36° x 36°	_	G. CIRCLE, & DIAG.	2	18" (VERT. CENTER)	67, 307	R6-2L, R6-2R	0.080*	ONE	1	K=1/2"	%" BLACK %" WHITE	24" X 30"	BLACK WHITE	BACKGROUND	_	2 12* (VERT.	CENTERO	3*; 27*				
		0.080*		R=1//2′	5%* BLACK 3%* WHITE			. CIRCLE, & DIAG.	2	12" (VERT. CENTER)	3"; 21"	R6-			R=1//2*	6 SERIES "D"	**			BA		21						
	R3-1	0.100*		R=21/4*	3%" BLACK 5%" WHITE		WHITE BACKGROUND.		2	18" (VERT.	6"; 30"	R6-1L, R6-1R	0.080*	ONE WAY	2	*0*	1/2" WHITE	36" X 12"	BLACK (WHITE ARROW) BLACK	ARROW & BORDER		2 as output creation	18" (VEK), CENIERO	1/2": 10//2"				
		0.080°		R=1½*	% BLACK % WHITE	24" X 24"	WHITE WHITE BACKGROIIND.	CIRCLE, & DIAG	2	12* (VERT. CENTER)	31, 217				J 	4* SERIES 'D"			BLA			-	2					
	R2-4a	0.125*	SPEED LIMIT 70 MINIMUM	8' SERIES 'E' R=3' 16' SERIES 'E' R=3' 8' SERIES 'C' 14' SERIES 'C'	% BLACK	48° X 96°	BLACK	BACKGROUND 1	91		4"; 28"; 52"; 60"; 92"	R5-la	0.100*	WRONG		8" SERIES "D"	1" WHITE	42" X 30"	WHJTE RED	ALL	-	4 .0	ŝ	3*,27*				
		0.125*		R=3* 8* SERIES "E* 8* SERIES "E* 16* SERIES "E*	1/4" BLACK 3/4" WHITE	.89 X .87	WHITE	B'GHUUND 1	9	,6	4*; 30"; 56"	R5-1	0.125*	LON OD		l	WHITE OUT- SIDE BORDER	48" X 48"	WHITE RED	ALL	-	4 9	n	4.; 44.				
	R2-1	0.100*	SPEED LIMIT 70	6. SERIES 'E' 6. SERIES 'E' 14" SERIES 'E'	% BLAC	36" X 48"	WHITE	B'GROUND 1	4	3.	91, 391	R	0.100"			R=1%* 4" SERIES "D"	WHITE OUT- SIDE BORDER	36° X 36°	WHITE	ALL	-	2 18* (VERT.	CENTER)	6"; 38"				
		2,088*		4" SERIES 'E' 4" SERIES 'E' 10" SERIES 'E'		2		B'GROUND 1	2	12" (VERT. CENTER)	3*; 27*	R6-3	0.080*	DIVIDED	HIGHWAY		%" BLACK %" WHITE	. 24*	BLACK WHITE	ROUND	1	2	CENTERO	3"; 21"				
		0.125"		3* R=4* 5* SERIES *C*	8" RED 11/2" WHE	68' TR		J ALL	4	15" (FROM CENTER)	3*; 21*	ěc	Ø.	NIQ VI	<u>₹</u>		e * %%	30° X 24'	BL WH	BACKGROUND		Address of the second	IS" (VERI), CENTER)	3,	SR THE	OWN ON		
	R1-2	0.100*	, AIEI	(R=3;	-	JIL. 48" EQUIL.		all 1	4	. 12*	3115"		0.125			R=3*	1/4" BLACK 3/4" WHITE	48" X 60"	BLACK	BACKGROUND	-	9 8	n	4"; 30"; 56"	NTITIES SHEET FI	HOWN. R2-4a WILL BE SI		
		0.125" 0.080"		R=2"	-	48" OCTAGON 36" EQUIL.		1 1 1	4 2	18* CE	39" 3": 27"	R4-7	00	5		R=21/4"	% BLACK % WHITE	36" X 48"	BLACK	BACKGROUND	_	2, 4	c	9, 39,	SUMMARY OF QUA	ED FROM THAT S		
	RI-I	0.100* 0.1		12" SERIES"C" 16" SERIES"C"		NCON		1 1 1	2 4	18" (VERT. 9"	3"; 33" 9"; 39"		0.080*			R=1//2"	% BLACK % WHITE	24" X 30"		QNND	1	2 2 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	VERI. CENIER/	3*; 27*	S LISTED ON THE	SIGNS ARE MODIF. ITS REQUIRED ON IN SHEETS.		
	SIGN NUMBER	ALUMINUM (6Ø61-T6) Ø SIGN BLANK THICKNESS Ø	TEGEND	LETTER & NAMERAL SPRES 12°S	NSIDE OUTSIDE		ONI	NUMBER OF POSTS	NUMBER OF HOLES TO BE PLINCHED (3%" DIA.)	E FROM GE	PUNCHING DISTANCE 3	SIGN NUMBER	ALUMINUM (6061-T6) SIGN BLANK THICKNESS	TEGEND			WIDTH OF BORDER OUTSIDE		COLORS COPY BACKGROUND		FOR MOUNTING	PUNCHED (%" DIA.) PUNCHING DISTANCE FROM		PUNCHING DISTANCE FROM TOP EDGE	GENERAL NOTES: 1. THE QUANTITIES, USETED ON THE SUMMARY OF DUANTITIES, SHEET FOR THE CONTRACTOR OF THE THE CONTRACT	EXCEPT WHERE STORY ARE WOOFFED FROM THAT SHOWN. 2. THE SPEED LIMITS REQUIRED ON STOAS R2-1 AND R2-40 WILL BE SHOWN ON INDIVIDUAL PLAN SHETS.		

4 Supplement to Notice To Bidders No.401- Cont'd.

													4	Supp	oler	nen	t t	o 1	NC	tic	e .	10	В	idders	NO		
PROJECT NO.	W4-101L W4-101R	0.125*	H=3°	1/4" BLACK 3/4" YELLOW	48" X 48" BLACK	YELLOW BACKGROUND			15" FROM VERT, CENTER															PORTATION			SN-3B SHEET NUMBER 6305
STATE MISS.	W4-1L W4-1R	0.125*	R=2//**	%" BLACK %" YELLOW	36" × 36" BLACK	8.4	1	2	VERT. CENTER	HORIZ, CENTER														T OF TRANS SIGN DIVISION RD PLAN	۵	GNS	117
	W3-3	0.125°	RE3*		48" X 48" BLACK	තී න	1	4	15" FROM VERT, CENTER	R HORIZ, CENTE														MISSISSIPPI DEPARTMENT OF TRANSPORTATION RAADRAY DESIGN DIVISION STANDARD PLAN	STANDARD	ADSIDE SI	MAY 01, 2017
		0.	R=2 ² /4*		36" X 36" BLACK	e e		2	VERT.	ER HORIZ, CENTE														MISSISSIPPI			ISSUE DATE:
	W3-2a	0.125*	MHITE RE3*		48" X 48" BLACK	8 €		4	15" FROM VERT, CENTER	ER HORIZ, CENT	W18-1	0.100*		X		.E.	34" BLACK /2" YELLOW	36" DIAMETER	YELLOW	BACKGROUND 1	2	15°	15" FROM HORIZ, CENTER	AH	NU	ISIA38	3140
			J. J. G		36" X 36" BLACK	മ്ഷ		2	TER CENTER	TER HORIZ, CENT				R	> //	3" 8" SERIES "	¾ BLACK 1/2° YELLOW	36.		BA			HOF				
	W3-1a	0.125*	WH.		6* 48" X 48" BLACK	മ്ഷ			15° FROM 3 VERT, CENTER	TER HORIZ, CEN	W13-3	0.125*	RAMP		МРН	8" SERIES "E" 16" SERIES "E" 6" SERIES "E" (SEE NOTE)	1//4" BLACK 3/4" YELLOW	48" × 60"	YELLOW	BACKGROUND 1	9	36	4"; 30"; 56"				
			% - N6 - H=2/A;	%* BLACK 5%* YELLOW	36" x 36" BLACK	YELLOW BACKGROUND & SYMBOL	-	2	CENTER	HORIZ, CENTER						R=3*											
	W1=7	0.100*		¾ BLACK /2° YELLOW	48" X 24" BLACK	YELLOW BACKGROUND	2	4	*on	3*; 21*	W13-2	0.125*	EXIT		MPH	8" SERIES "E" 16" SERIES "E" 6" SERIES "E" (SEE NOTE)	1/4" BLACK ¾4" YELLOW	48" × 60"	YELLOW	BACKGROUNU 1	٠	.6	4"; 30"; 56"				
	W1-6L W1-6R	0.100*	W:-18	% BLACK 1/2" YELLOW	48" X 24" BLACK	YELLOW BACKGROUND	2	4	ò	3*; 21*	W13-1	0.080°		W) E	2,2		%, BLACK %, YELLOW		YELLOW	BACKURUUND 1	2	12" (VERT, CENTER)	3*; 21*				
	7 ~	*	R: 3,	1/4" BLACK 34" YELLOW	48" × 48" BLACK	YELLOW BACKGROUND	-	ч	VERT, CENTER	HORIZ, CENTER							1/4" BLACK %" YELLOW	48" × 48"	YELLOW	BACKGROUND 1	4	15" FROM VFRT, CFNTFR	15" FROM HORIZ, CENTER				
	W1-4L W1-4R	#.125*	R=2)/4*	% BLACK % YELLOW	36" × 36" BLACK	YELLOW BACKGROUND	1	2	VERT. CENTER	HORIZ, CENTER	C-9M	0.125*				R=21/4"	% BLACK % YELLOW	36" × 36"	YELLOW	BACKGROUND 1	2		18" FROM HORIZ, CENTER				
	W1-3L W1-3R	0.125*	F=3.	1/4" BLACK 34" YELLOW	48" X 48" BLACK	YELLOW BACKGROUND		4	VERT, CENTER	HORIZ, CENTER	W6-2	0.125"				»——	1/4" BLACK 3/4" YELLOW	48" X 48"	_	BACKGROUND 1	4	15" FROM VFRT, CFNTFR	15" FROM HORIZ, CENTER				
	W	0.	R=2//4	% BLACK % YELLOW	36" X 36" BLACK	BA	-		VERT.	HORIZ, CENT	*	0					% BLACK % YELLOW	36" X 36"	4	BACKGROUND 1	2	VERT.	18" FROM R HORIZ, CENTER		Ę.		
	W1-2L W1-2R	0.125*			48" X 48" BLACK	80		4	VERT, CENTER	R HORIZ, CENTER	1-9M	0.125*	(»—	1/4" BLACK 74" YELLOW	-	-	ID BACKGROUND	4	15° FROM VERT, CENTE	15" FROM TRIZ. CENTER		EET FOR THE OR FINAL PAYMEN	AND NUMERALS SHT.	L BE SHOWN
			R=2/.4*		36" X 36" BLACK	8	-	2	TER CENTER	TER HORIZ, CENTE			~ ×				K 7g" BLACK W 5/g" YELLOW	.	_	ND BACKGROUND 1	2	FR CENTER	TER HORIZ, CENTER		F QUANTITIES SH AS THE BASIS F HAT SHOWN.	OF THE LETTER OR NUMERAL HEIG	2 AND W13-3 W1L
	W1-1L W1-1R	0.125*			5" 48" X 48" BLACK	80	-	4	15" FROM VERT, CENTER	TER HORIZ, CEN	W4-2	0.125*	NOTE: SEE PLAN SHEETS FOR IDEOGRAM REQUIRED ON INDIVIDUAL SIGNS.	<u></u>		» —	K 1/4" BLACK DW 3/4" YELLOW	-	-	JND BACKGROUND	4	15" FRON	15" FROM TER HORIZ, CENTER		I THE SUMMARY O ET WILL BE USED MODIFIED FROM T	HE STROKE WIDTH OF THE LETTER	SIGNS WIB-1, WIB-
		9	R-27/4.		36" X 36" BLACK	YELLOW BACKGROUND	-	Ж. 2		HORIZ, CENTER	1		NOTE: SEE IDEO! INDIV				IDE % YELLOW	M)		BACKGROUND 1	3E 2	T	18" FROM HORIZ, CENTER		1. THE QUANTITES, LISTED ON THE STAMMARY OF QUANTITIES, SHEET FOR THE ENGINE SHOWN ON THIS SHEET MILL BE USED AS THE BASIS FOR FINAL PAYMENT, EXCEPT WHERE SIGNS ARE WODIFIED FROM THAT SHOWN.	2. SIGNS W13-2 AND W13-3- THE SIROKE WIDTH OF THE LETTER AND NUMERALS SHALL BE WIDENED TO 20% OF THE LETTER OR NUMERAL HEIGHT.	3. THE SPEEDS REQUIRED ON SIONS WIB-1, WIB-2 AND WIB-3 WILL BE SHOWN ON INCLVIDUAL PLAN SHEETS.
	SIGN NUMBER	ALUMINUM (6061-T6) SIGN BLANK THICKNESS	LEGEND	LETTER & NUMERAL SERIES INSIDE WIDTH OF BORDER OUTSIDE	SIZE (WIDTH X HEIGHT)	REFLECTORIZATION	NUMBER OF POSTS FOR MOUNTING	NUMBER OF HOLES TO BE PUNCHED (3/2" DIA.)	FUNCHING DISTANCE FROM EACH VERT, EDGE	FUNCHING DISTANCE FROM TOP EDGE	SIGN NUMBER	SIGN BLANK THICKNESS		LEGEND		LETTER & NUMERAL SERIES	WIDTH OF BORDER OUTSIDE	Ė	COLORS BACKGROUND	NUMBER OF POSTS	NUMBER OF HOLES TO BE PLINCHED (%" DIA.)	PUNCHING DISTANCE FROM	PUNCHING DISTANCE FROM TOP EDGE	GENERAL NOTES:	1. THE QUANT SIGNS SHO EXCEPT WH	2. SIGNS W13 SHALL BE	3. THE SPEEL ON INDIVI