COUNTY LINE TOWN CORPORATION LINE SECTION LINE EXISTING ROAD OR TRAVELED WAY PROPOSED ROAD OR TRAVELED WAY RAILROAD SURVEY LINE BRIDGES

LENGTH DATA

ENGTH OF ROADWAY	52,457.900 FT.	9.935 MI.
ENGTH OF BRIDGES	0.000 FT.	0.000 MI.
ENGTH OF PROJECT (NET)	52,457.900 FT.	9.935 MI.
ENGTH OF EXCEPTIONS	0.000 FT.	0.000 MI.
ENGTH OF PROJECT (GROSS)	52,457.900 FT.	9.935 MI.



MENT OF TRANSPORTATION	
OF	
PI DEPART	
MISSISSIP	

TOTAL SHEETS (41)

DESCRIPTION OF SHEET	WKG. NO.	SH. NO.
TITLE AND LAYOUT SHEET (1)		1
DETAILED INDEX (1) GENERAL NOTES (1)	DI-1 GN-1	2 3
TYPICAL SECTION SHEETS (1) TYPICAL SECTION - SR 35	TS-1	4
QUANTITY SHEETS (3) SUMMARY OF QUANTITIES ESTIMATED QUANTITY FOR MILLING, ASPHALT, AND GRANULAR MATERIAL ESTIMATED QUANTITIES FOR TRAFFIC CONTROL SIGNS	SQ-1 EQ-1 TCPQ-1	5 6 7
PLAN & PROFILE SHEETS (18) STA. 15+97.73 TO STA. 35+00 STA. 35+00 TO STA. 85+00 STA. 65+00 TO STA. 95+00 STA. 65+00 TO STA. 95+00 STA. 95+00 TO STA. 155+00 STA. 155+00 TO STA. 155+00 STA. 155+00 TO STA. 185+00 STA. 155+00 TO STA. 185+00 STA. 185+00 TO STA. 215+00 STA. 215+00 TO STA. 245+00 STA. 215+00 TO STA. 245+00 STA. 275+00 TO STA. 305-00 STA. 275+00 TO STA. 335+00 STA. 365+00 TO STA. 335+00 STA. 365+00 TO STA. 355+00 STA. 365+00 TO STA. 455+00 STA. 365+00 TO STA. 455+00 STA. 455+00 TO STA. 455+00 STA. 455+00 TO STA. 515+00 STA. 455+00 TO STA. 515+00 STA. 515+00 TO STA. 515+00 STA. 515	WK3 WK4 WK5 WK6 WK7 WK8 WK9 WK10 WK11 WK12 WK13 WK14 WK15 WK16 WK17 WK18 WK19 WK20	8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25
STANDARD DRAWINGS (12) PAVEMENT MARKING DETAILS FOR 2-LANE AND 4-LANE DIVIDED HIGHWAYS PAVEMENT MARKING LEGEND DETAILS PAVEMENT MARKING LEGEND DETAILS 2-WAY RAISED PAVEMENT MARKERS AT INTERSECTING ROADS (2-LANE) TRAFFIC CONTROL PLAN WITH FLAGGER (ONE-LANE CLOSURE OF TWO-WAY TRAFFIC) HIGHWAY SIGN AND BARRICADE DETAIL FOR CONSTRUCTION PROJECTS TRAFFIC CONTROL PLAN FOR MOBILE OPERATIONS MULTILANE ROADS AND IWO-LANE ROADS TRAFFIC CONTROL PLANS UNEVEN PAVEMENT DETAILS TEMPORARY STRIPING FOR TRAFFIC CONTROL 2-LANE AND 4-LANE DIVIDED HIGHWAYS LOCATION OF R16-3 SIGNS (SPEEDING FINES DOUBLED) TRAFFIC CONTROL DETAILS DRUM PLACEVENT AND SHOULDER CLOSURE RURAL DRIVEWAYS	PM-1 PM-5 PM-6 PM-11 TCP-1 TCP-8 TCP-9 TCP-12 TCP-13 TCP-15 TCP-16 RD-1	6Ø51 6Ø55 6Ø56 6Ø61 6351 6358 6359 6362 6365 6365 6366

DISTRICT 7

PS & E PLANS-DATE 03/12/2021			
FMS CON. # 108367/301000			
REVISIONS			
DATE	SHEET NO.	BY	
04/23/21	5	K.C.	

		ВҮ	MISSISSIPPI I	DEPARTMENT	OF TRAN	SPORTATION
		SION	DETAILED I	INDEX		OF TRANSPOR
		REVI	PROJ. NO.: S' COUNTY: SMI	TP-0023-01(087) ITH		WORKING NUMBE

쁜 FILE NAME: (Ø2)index.dgn

SHEET NUMBER

PROJECT NO.

GENERAL NOTES

- THE LOCATION AND SPACING OF SIGNS, SHOWN ON THE TRAFFIC CONTROL PLANS, ARE APPROXIMATE AND MAY BE ADJUSTED AS NECESSARY TO FIT FIELD CONDITIONS.
- (2) ALL TRAFFIC CONTROL DEVICES ON THIS PROJECT SHALL COMPLY WITH PART VI OF THE MUTCD (LATEST EDITION).
- ALL PLASTIC DRUMS SHALL HAVE A BALLASTING COLLAR MADE FROM RECYCLED TRUCK TIRES OR OTHER SUITABLE MATERIAL.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING EXISTING STRUCTURES SUCH AS, BUT NOT LIMITED TO, PIPES, INLETS, APRONS, AND BRIDGES FROM DAMAGE WHICH MIGHT OCCUR DURING CONSTRUCTION. THE CONTRACTOR SHALL REPLACE OR REPAIR, AS DIRECTED BY THE ENGINEER, ANY STRUCTURES DAMAGED DURING THE LIFE OF THE CONTRACT. NO PAYMENT WILL BE MADE FOR REPLACEMENT OR REPAIR OF DAMAGED ITEMS.
- 5 FLUORESCENT ORANGE SHEETING SHALL BE USED ON ALL CONSTRUCTION AND TRAFFIC CONTROL SIGNS EXCEPT FOR THOSE DESIGNATED ON THE PLANS TO BE BLACK LEGEND AND BORDER ON WHITE BACKGROUND.
- (6) VEGETATIVE MATERIAL WILL BE REMOVED PRIOR TO PLACEMENT OF GRANULAR MATERIAL. THE COST OF WHICH SHALL BE ABSORBED IN OTHER ITEMS BID.
- (7) THE CONTRACTOR SHALL COVER ANY TEMPORARY TRAFFIC CONTROL SIGNS SHOWN IN THE TRAFFIC CONTROL PLAN THAT DO NOT APPLY TO THE CURRENT PHASE.
- REMOVAL OF RAISED PAVEMENT MARKERS THAT ARE IN CONFLICT WITH REQUIRED CONSTRUCTION IS NOT CONSIDERED A SEPARATE PAY ITEM. COST TO BE ABSORBED IN OTHER ITEMS BID.
- (9) WHERE MILLING IS REQUIRED, THE CONTRACTOR SHALL PROVIDE OUTLETS IN THE EXISTING SHOULDERS AT SUFFICIENT INTERVALS TO PREVENT POOLING OR STANDING WATER ON THE MILLED SURFACE, THE COST OF WHICH SHALL BE ABSORBED IN OTHER ITEMS BID.
- TEMPORARY STRIPING SHALL CONFORM TO FINISHED STRIPE SPECIFICATIONS FOR ALIGNMENT, NEATNESS, AND STRAIGHTNESS.
- (1) ALL ADDENDA TO THESE PLANS WILL BE POSTED TO WWW.MDOT.MS.GOV UNDER THE PROPOSAL ADDENDA COLUMN. BIDDERS ARE ADVISED THAT HARD COPIES OF ANY ADDENDA FOR THIS PROJECT WILL NOT BE MAILED. IT IS THE BIDDER'S RESPONSIBILITY TO CHECK AND SEE IF ANY ADDENDA HAVE BEEN POSTED FOR THIS PROJECT
- 12 STORAGE OF FLAMMABLE MATERIALS WILL NOT BE ALLOWED UNDER ANY BRIDGE STRUCTURES WITHOUT WRITTEN APPROVAL FROM THE PROJECT ENGINEER. SEE NOTICE TO BIDDERS ENTITLED "MATERIAL STORAGE UNDER BRIDGES" FOR MORE INFORMATION.
- (13) THE RETROREFLECTIVE SIGN SHEETING ON RIGID, TEMPORARY TRAFFIC CONTROL (ORANGE) SIGNS SHALL BE MINIMUM TYPE IX.
- 4 ALL SIGNS AND DELINEATORS THAT CONFLICT WITH THE CONSTRUCTION OF THIS PROJECT SHALL BE REMOVED AND RESET BY THE CONTRACTOR; COST TO BE ABSORBED IN OTHER PAY ITEMS.
- (15) ALL ASPHALT AND CONCRETE CURBS ALONG RAMPS, LOCAL ROADS, ETC. FROM B.O.P. TO E.O.P.SHALL BE PAINTED (TWO APPLICATIONS) WITH WHITE TRAFFIC PAINT AND TRAFFIC BEADS; COST TO BE ABSORBED IN OTHER PAY ITEMS.
- 16 IF THE ASPHALT CURB ALONG THE LOCAL ROAD IS SEVERELY DAMAGED, THE ENTIRE ASPHALT CURB WILL BE REMOVED AS DIRECTED BY THE ENGINEER: COST TO BE ABSORBED IN OTHER PAY ITEMS.
- TEMPORARY STRIPING SHALL BE REQUIRED AFTER MILLING AND OVERLAYING OPERATIONS; TEMPORARY STRIPING SHALL BE PLACED IN THE SAME LOCATIONS AND LAYOUT AS PERMANENT STRIPE. ALL CENTERLINE, LANE LINES, EDGE LINES, AND NO-PASSING STRIPES THAT HAVE BEEN REMOVED DURING THE DAY'S OPERATIONS SHALL BE REPLACED WITH TEMPORARY STRIPE BEFORE WORK IS DISCONTINUED FOR THE DAY OR AS SOON THEREAFTER AS WEATHER CONDITIONS WILL PERMIT, EXCEPT THAT:
 - (1) REPLACEMENT OF NO-PASSING STRIPES MAY BE DELAYED FOR A PERIOD NOT TO EXCEED THREE (3) DAYS FOR A TWO OR THREE LANE ROAD
 - (2) TEMPORARY EDGE LINES ON PROJECTS REQUIRING SHOULDERS CONSTRUCTED OF GRANULAR MATERIAL MAY BE DELAYED FOR A PERIOD NOT TO EXCEED THREE (3) DAYS.
- (18) ALL LOCAL ROADS SHALL BE PAVED TO THE R.O.W. LIMITS OR AS DIRECTED BY THE ENGINEER.
- (19) GRANULAR MATERIAL WILL NOT BE ALLOWED TO BE PLACED DIRECTLY ON THE SURFACE LIFT OF ASPHALT, BUT MUST BE $^\prime$ PLACED DIRECTLY ON THE GRAVEL SHOULDER OR A ROAD WIDENER MACHINE USED AND APPROVED BY THE PROJECT ENGINEER.
- 200 ALL RAMPS AND DRIVEWAY PADS SHALL BE PAVED TO THE SHOULDER LINE, MINIMUM OR FURTHER, AS DIRECTED BY THE ENGINEER WITHIN THE R.O.W. LIMITS.
- (21) NO TEMPORARY CULVERT STREAM CROSSINGS WILL BE ALLOWED.
- 22 SOME WORK IS REQUIRED OUTSIDE THE PROJECT LIMITS. NO ADDITIONAL COMPENSATION WILL BE MADE FOR SUCH WORK EXCEPT AS PROVIDED BY SPECIFIC PAY ITEMS INCLUDED IN THE PLANS
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING EXISTING BRIDGE JOINT MATERIAL ON ALL BRIDGES WITHIN THE PROJECT LIMITS FROM DIRECT CONTACT WITH THERMOPLASTIC PAVEMENT MARKING, AND WITH ANY OTHER CONSTRUCTION MATERIALS THAT MIGHT DAMAGE THE BRIDGE JOINTS.
- TEMPORARY PAVEMENT JOINTS (PAPER JOINTS) SHALL BE EMPLOYED AT ALL LOCATIONS REQUIRING TRAFFIC TO TRAVERSE AN UNEVEN PAVEMENT JOINT. PAPER JOINTS SHALL BE A MINIMUM OF OF 9 FEET IN LENGTH AND SHALL BE ADEQUATELY MAINTAINED.

GENERAL NOTES (CONT.)

