GENERAL INDEX				
	INCLUDED THIS PROJECT			
X	ROADWAY	1		
X	PERMANENT SIGNS	1001		
	TRAFFIC SIGNALS	2001		
	ITS COMPONENTS	3001		
	LIGHTING	4001		
	(RESERVED)	5001		
X	ROADWAY STD. DWGS	6001		
	BOX CULVERT STD. DWGS (LRFD)	7001		
	BOX CULVERT STD. DWGS (STD. SPI	EC.)7501		
	BRIDGE	8001		
X	CROSS SECTIONS	9001		

BRIDGE STRUCTURES REQ'D.

BOX BRIDGES REQ'D.


NONE

NONE

STATE OF MISSISSIPPI MISSISSIPPI DEPARTMENT OF TRANSPORTATION

PLAN AND PROFILE OF PROPOSED STATE HIGHWAY FEDERAL AID PROJECT NO. HSIP-0008-03(062)

US 49 at RT Braddy Rd & US 49 at Muse Rd RANKIN COUNTY



1 IN.= 50 FT. 1 IN.= 5 FT.

1 IN. = 2,000 FT.

CONVENTIONAL SYMBOLS

COUNTY LINE

TOWN CORP LINE

SECTION LINE

SECTION LINE

DEED LINE

DEED LINE

EXISTING ROADWAY

PROPOSED ROADWAY

RAILROAD

BRIDGES

EQUATIONS

LENGTH DATA

4,890 FT. 0.926 MI.

4,890 FT. 0.926 MI.

4,890 FT. 0.926 MI.

0 FT. 0 MI.

0 FT. 0 MI.

LENGTH OF ROADWAY

LENGTH OF PROJECT (NET)

LENGTH OF PROJECT (GROSS)

LENGTH OF EXCEPTIONS

LENGTH OF BRIDGES

EXCEPTIONS

STA. 310+94.360 R4 (BK) = STA. 311+18.740 (AH) R5

PROFILE


LAYOUT

NONE





STATE	PROJECT NUMBER	SHEET NO.	
MISSISSIPPI	HISP-0008-03(062)	1	



DESIGN CONTROL

65 MPH = V (SPEED DESI

ADT (2021) = 23,000: ADT (2031) = 27,60DHV = 2.300: D = 50% T = 18%

PERMITS ACQUIRED BY MDOT

WETLANDS AND WATERS PERMITS

	WATERS	WETLANDS
NATIONWIDE #14	N	N
NATIONWIDE (OTHER)*	N	N
GENERAL*	N	N
INDIVIDUAL (404)*	N	N

STORMWATER PERMIT S

- Y REQUIRED, CNOI SUBMITTED BY MDOT (DISTURBED AREA=5 ACRES)
- S REQUIRED, SCNOI TO BE SUBMITTED BY CONTRACTOR (1 TO 4.99 ACRES)
- N NO STORMWATER PERMIT REQUIRED (<1 ACRE)

APPROVED BY:

DESIGNED BY: BENCHMARK ENGINEERING & SURVEYING, LLC.

CONSTRUCTION	PROJECT DATA
EXTERNAL PROJECT NUMBER	HSIP-0008-03(062)
FMS & DETAIL	109122/301000

P S & E DATE: 05/20/2024

APPROVED:


DEPUTY EXECUTIVE DIRECTOR / CHIEF ENGINEER

EXECUTIVE DIRECTOR

3:41:14 PM TITLE_SH.

DATE





DECCRIPTION OF CHEET	WKG.	SH.	DECCRIPTION OF CHEET	WKG.	SH.
DESCRIPTION OF SHEET	NO	<u>NO.</u>	DESCRIPTION OF SHEET	NO	NO.
ROADWAY					
TITLE SHEET (1)		1	CONSTRUCTION SIGNING & TRAFFIC CONTROL PLAN (6)		
DETAILED INDEX & GENERAL NOTES (4)			CONSTRUCTION SIGNING - U.S. 49	CS-1	49
			CONSTRUCTION SIGNING - MUSE ROAD	CS-2	50
DETAILED INDEX DETAILED INDEX	DI-1 DI-2	2	CONSTRUCTION SIGNING - DIXIE ROAD/RT BRADDY ROAD CONSTRUCTION SIGNING - U.S. 49	CS-3 CS-4	51 52
GENERAL NOTES	GN-1	4	TRAFFIC CONTROL PLAN - PHASE 1	TC-1	53
GENERAL NOTES	GN-2	5	TRAFFIC CONTROL PLAN - PHASE 2 TRAFFIC CONTROL PLAN - PHASE 3	TC-2 TC-3	54 55
TYPICAL SECTIONS (11)			TRAFFIC CONTROL PLAN - PHASE 3	TC-4	56
TYPICAL SECTION - U.S. 49	TS-1	6	TRAFFIC CONTROL PLAN - PHASE 3 TRAFFIC CONTROL PLAN - PHASE 3	TC-5	57 58
TYPICAL SECTION - 0.5. 49 TYPICAL SECTION - U.S. 49	TS-2	7	TRAFFIC CONTROL PLAN - PHASE 3 TRAFFIC CONTROL PLAN - PHASE 3	TC-6 TC-7	50 59
TYPICAL SECTION - U.S. 49	TS-3	8	TRAFFIC CONTROL PLAN - PHASE 3	TC-8	60
TYPICAL SECTION - MUSE ROAD TYPICAL SECTION - U.S. 49	TS-4 TS-5	9 10	TRAFFIC CONTROL PLAN - PHASE 3 TRAFFIC CONTROL PLAN - PHASE 3	TC-9 TC-10	61 62
TYPICAL SECTION - 0.5. 49 TYPICAL SECTION - U.S. 49	TS-6	11	TRAFFIC CONTROL PLAN - PHASE 3	TC-10	63
TYPICAL SECTION - U.S. 49	TS-7	12	TRAFFIC CONTROL PLAN - PHASE 3	TC-12	64
TYPICAL SECTION - DIXIE ROAD/RT BRADDY ROAD TYPICAL SECTION - U.S. 49	TS-8 TS-9	13 14	PAVEMENT MARKING DEATILS (3)		
TYPICAL SECTION - GRATE INLET RELOCATION	TS-10	15	TAVEMENT MARKING DEATIES (S)		
TYPICAL SECTION - MEDIAN & ISLAND PAVEMENT DETAILS	TS-11	16	U.S. 49 AT MUSE ROAD	PMD-1	58
TYPICAL SECTION - SLOTED CURB DETAILS	TS-12	17	U.S. 49 AT DIXIE ROAD/RT BRADDY ROAD U.S. 49	PMD-2 PMD-3	59 60
QUANTITY SHEETS (7)				ל שויו ז	00
SUMMARY OF QUANTITIES	SQ-1	18	MISCELLANEOUS - SPECIAL DESIGN SHEETS (3)		
SUMMARY OF QUANTITIES	SQ-2	19	VEGETATION SCHEDULE	VS-1	61
ESTIMATED QUANTITIES - CURB & MEDIAN ISLAND PAVEMENT, REMOVAL ITEMS, AND DRAINAGE STRUCTURES	EQ-1	20	RUMBLE STRIPS FOR 4-LANE DIVIDED ROADWAYS WITH 2-FOOT PAVED SHOULDER	RS-6	62
ESTIMATED QUANTITIES - PAVEMENT MARKING AND TRAFFIC CONTROL ITEMS ESTIMATED QUANTITIES - STANDARD ROADSIGN SIGNS	EQ-2 EQ-3	21 22	LANE CLOSURE DETAILS FOR GREATER THAN 3 INCH DROPOFF	SDTCP-C	63
ESTIMATED QUANTITIES - TRAFFIC CONTROL SIGNS	EQ-4	23	PERMANENT SIGNING PLAN (3)		
ESTIMATED QUANTITIES - FULL DEPTH REPAIR, UNDERSEALING & ESTIMATED EARTHWORK QUANTITIES	EQ-5	24	LLC 40 AT MUCE BOAD	DCD 1	1001
PLAN AND PROFILE SHEETS (10)			U.S. 49 AT MUSE ROAD U.S. 49 AT DIXIE ROAD/RT BRADDY ROAD	PSP-1 PSP-2	1001 1002
U.S. 49 RIGHT STA. 288+70 - 279+00	2DT	25	U.S. 49	PSP-3	1003
U.S. 49 LEFT STA. 288+70 - 279+00	3RT 3LT	25 26	ROADWAY DESIGN STANDARD DRAWINGS (67)		
MUSE ROAD STA. 11+58.10 - 13+08.75	3A	27			
MUSE ROAD STA. 10+00 - 11+89.85 U.S. 49 RIGHT STA. 319+00 - 333+00	3B 4RT	28 29	CONCRETE ISLAND PAVEMENT DETAILS PAVEMENT MARKING DETAILS FOR 2-LANE & 4 LANE DIVIDED HIGHWAY	CIP-1 PM-1	6011 6051
U.S. 49 LEFT STA. 319+00 - 333+00	4LT	30	PAVEMENT MARKING DETAILS FOR 2-LANE & 4 LANE DIVIDED HIGHWAT PAVEMENT MARKING LEGEND DETAILS	PM-1 PM-5	6055
DIXIE ROAD STA. 11+57.87 - 12+92.41	4A	31	PAVEMENT MARKING LEGEND DETAILS	PM-6	6056
RT BRADDY ROAD STA. 10+00 - 11+82.85 U.S. 49 RIGHT STA. 333+00 - 337+43 (EOP)	4B 5RT	32 33	TYPICAL PAVEMENT MARKING DETAIL FOR MEDIAN CROSSOVERS 2-WAY RAISED PAVEMENT MARKERS AT INTERSECTING ROADS (4-LANE)	PM-9 PM-12	6059 6062
U.S. 49 LEFT STA. 333+00 - 337+43 (EOP)	5LT	34	RUMBLE STRIPES 4 LANE HIGHWAYS	RS-2	6065
			TYPICAL TEMPORARY EROSION CONTROL/SEDIMENT CONTROL APPLICATIONS	ECD-1	6101
EROSION CONTROL SHEETS (7)			DETAILS OF SEDIMENT BARRIER APPLICATIONS DETAILS OF SILT FENCE INSTALLATION	ECD-2 ECD-3	6102 6103
U.S. 49 STA. 288+70 - 279+00	ECP-1	35	DITCH CHECK STRUCTURES, TYPICAL APPLICATIONS AND DETAILS	ECD-4	6104
MUSE ROAD STA. 11+58.10 - 13+08.75	ECP-2	36 27	TEMPORARY EROSION, SEDIMENT, AND WATER POLLUTION MEASURES	ECD-5	6105
MUSE ROAD STA. 10+00 - 11+89.85 U.S. 49 RIGHT STA. 319+00 - 333+00	ECP-3 ECP-4	37 38	DETAILS OF EROSION CONTROL WATTLE DITCH CHECK DETAILS OF EROSION CONTROL SILT DIKE DITCH CHECK	ECD-6 ECD-7	6106 6107
U.S. 49 RIGHT STA. 333+00 - 337+43 (EOP)	ECP-5	39	ROCK DITCH CHECK	ECD-8	6108
DIXIE ROAD STA. 11+57.87 - 12+92.41 RT BRADDY ROAD STA. 10+00 - 11+82.85	ECP-6 ECP-7	40 41	ROCK FILTER DAM ROCK DITCH CHECK WITH SUMP EXCAVATION AND ROCK FILTER DAM	ECD-9 ECD-10	6109 6110
NI BRADDI ROAD STA. 10+00 - 11+02.05	LCF-7	41	TYPICAL APPLICATIONS AND DETAILS FOR INLET CONSTRUCTION	ECD-10	6111
INTERSECTION DETAILS (4)			INLET PROTECTION OF WATELES	ECD-12	6112
U.S. 49 AT MUSE ROAD	ID-1	42	INLET PROTECTION OF WATTLES INLET PROTECTION DETAILS OF MANUFACTURED INLET PROTECTION DEVICE	ECD-13 ECD-14	6113 6114
U.S. 49 AT MUSE ROAD	ID-2	43	INLET PROTECTION OF SANDBAGS	ECD-15	6115
U.S. 49 AT DIXIE ROAD/RT BRADDY ROAD	ID-3	44	STABILIZED CONSTRUCTION ENTRANCE	ECD-16	6116
U.S. 49 AT DIXIE ROAD/RT BRADDY ROAD	ID-4	45	TEMPORARY STREAM DIVERSION TEMPORARY STREAM DIVERSION (BOX EXTENSION)	ECD-18 ECD-19	6118 6119
FORM GRADES (3)			FLOATING TURBIDITY CURTAIN	ECD-20	6120
FORM GRADES - U.S. 49 AT MUSE ROAD	FG-1	46	DETAILS OF EROSION CONTROL SANDBAG DITCH CHECK SEDIMENT RETENTION BARRIER	ECD-21 ECD-22	6121 6122
FORM GRADES - U.S. 49 AT MUSE ROAD/RT BRADDY ROAD	FG-1 FG-2	46 47	DETAILS OF TYPICAL DITCH TREATMENTS	DT-1	6123
FORM GRADES - U.S. 49	FG-3	48	TYPICAL TEMPORARY EROSION CONTROL MEASURES (SLOPE DRAIN AND TYPE A SILT BASIN)	BAS-A	6125
			EROSION CONTROL BLANKET CONCRETE MEDIAN BARRIER	ECB-1 CMB-3	6131 6226
			STANDARD DIRECTIONAL (GUIDE) SIGNS	SN-1	6301
			ROUTE SHIELDS AND "EXIT ONLY" PANELS	SN-2	6302
			STANDARD ROADSIDE SIGNS STANDARD ROADSIDE SIGNS	SN-3 SN-3A	6303 6304
			STANDARD ROADSIDE SIGNS	SN-3B	6305

			MISSISSIBBI DEBABTMENT OF T	MISSISSIFTI DEL'ANTIMENT UL T
DESIGNED BY: B.E.S. DESIGN TEAM	DEIAILED BY: KUK	CHECKED BY: OLB		DATE: 05/20/24
FMS CON: 109122/301000	Cacked and aran . CM Tailoga	PRUJECI NO.: HSIP-UUU0-US(U02)		COUNTY: RANKIN

DETAILED IN

WK. NO. **DI-1**

SHEET NO.





DESIGN

HSIP-0008-03(062)

PROJECT NO.: HSIF

122/301000

FMS CON: 109

OF TRANSPOR	NOITATE

DESCRIPTION OF SHEET	WKG. NO.	SH. NO.
ROADWAY DESIGN STANDARD DRAWINGS (CONTINUED)		
STANDARD ROADSIDE SIGN ASSEMBLY AND INSTALLATION STANDARD ROADSIDE SIGN ASSEMBLY AND INSTALLATION TANDARD ROADSIDE SIGN ASSEMBLY AND INSTALLATION TYPICAL INSTALLATION OF GROUND MOUNTED DIRECTIONAL SIGNS BREAKWAY SIGN SUPPORTS BREAKWAY SIGN SUPPORTS BREAKWAY SIGN SUPPORTS SIGN FACE CONST. AND ATTACHMENT OF GROUND MOUNTED DIRECTIONAL SIGNS TO STEEL BEAMS TYPICAL CROSSOVER DELINEATION SIGN SUPPORT HARDWARE 2.0" SQUARE POST SIGN SUPPORT HARDWARE 2.5" SQUARE POST SIGN SUPPORT HARDWARE 2.5" SQUARE POST TRAFFIC CONTROL PLAN WITH FLAGGER (ONE-LANE CLOSURE OF TWO-WAY TRAFFIC) TRAFFIC CONTROL PLAN FOR POSTED SPEED LIMIT OF 65 MPH OR 70 MPH (INTERSTATES AND OTHER 4-LANE DIVIDED HIGHWAYS) (MEDAIN LANE OR OUTSIDE LANE CLOSURE)(EXTENDED PERIOD) TRAFFIC CONTROL PLAN FOR POSTED SPEED LIMIT OF 65 MPH OR 70 MPH (INTERSTATES AND OTHER 4-LANE DIVIDED HIGHWAYS) (MEDAIN LANE OR OUTSIDE LANE CLOSURE)(WORK DAY ONLY) HIGHWAYS) (MEDAIN LANE OR OUTSIDE LANE CLOSURE)(WORK DAY ONLY) HIGHWAYS) (MEDAIN LANE OR OUTSIDE LANE CLOSURE)(WORK DAY ONLY) HIGHWAYS SIGN AND BARRICADE DETAILS FOR CONSTRUCTION PROJECTS TRAFFIC CONTROL PLAN HOBILE OPERATIONS MULTILANE ROADS AND TWO-LANE ROADS TRAFFIC CONTROL PLAN : UNEVEN PAVEMENT DETAILS TEMPORARY STRIPING FOR TRAFFIC CONTROL 2-LANE AND 4-LANE DIVIDED HIGHWAY LOCATION OF R16-3 SIGNS (SPEEDING FINES DOUBLED) TRAFFIC CONTROL DETAILS DRUM PLACEMENT AND SHOULDER CLOSURE TYPICAL GRADING TRANSITION BETWEEN CUTS AND FILLS DRIVEWAYS, CURB AND GUTTER, AND SIDEWALK MISCELLANEOUS DETAILS SHEET 1, STACKED PIPE JOINTS, EXCAVATION AT GRADE POINTS DETAILS OF PAVED FILLMES PIPE CULVERT INSTALLATION CONCRETE PIPE COLLAR JUNCTION BOX FOR PIPE CULVERTS TYPE 1 MEDIAN INLET! FOR BOX CULVERTS	SN-4 SN-4A SN-4B SN-5 SN-6 SN-6A SN-6B SN-7 SN-8B SN-10C SN-10D TCP-1 TCP-4 TCP-5 TCP-13 TCP-12 TCP-13 TCP-15 TCP-16 GT-1 SD-1 MDS-1 PF-1 PI-1 PC-1 JB-1 MI-3	6306 6307 6308 6309 6310 6311 6312 6313 6316 6323 6324 6351 6354 6355 6365 6365 6365 6365 6404 6419 6425 6426 6501 6503 6504 6508 6513
DETAIL OF GRATES FOR MEDIAN INLETS FLARED END SECION FOR CONCRETE PIPE	IG-1 FE-1	6516 6530
CROSS SECTIONS (11) U.S. 49		0001 0011

TOTAL SHEETS = 144

9001-9011

WK. NO. **DI-2** SHEET NO.

GENERAL NOTES







WK. NO. GN-1 SHEET NO.

BRIDGES AND WALLS

STORAGE OF FLAMMABLE MATERIALS WILL NOT BE ALLOWED UNDER ANY BRIDGE STRUCTURES WITHOUT WRITTEN APPROVAL FROM THE PROJECT ENGINEER. SEE NOTICE TO BIDDERS ENTITLED "MATERIAL STORAGE UNDER BRIDGES" FOR MORE INFORMATION.

DRAINAGE STRUCTURES

- ALL PIPE JOINTS ARE TO BE WRAPPED IN 24-INCH WIDE TYPE V GEOTEXTILE FABRIC. ALL PICKUP HOLES SHALL BE PLUGGED AND COVERED WITH TYPE V GEOTEXTILE FABRIC . THE COST OF WHICH SHALL BE ABSORBED IN OTHER ITEMS
- CURB AND GUTTER VERTICAL DIMENSIONS SHOWN IN THE DETAIL DRAWINGS ARE FOR A CURB IN THE "CATCH" CONFIGURATION AND SHALL BE CONSIDERED TO BE MINIMUM DIMENSIONS. THE DIMENSIONS MAY BE MODIFIED AS NECESSARY FOR "SPILL" CURB AND GUTTER, BUT SHALL NOT BE LESS THAN THE MINIMUM SHOWN.
- THE COST FOR REMOVAL OF ALL HEADWALLS AND WINGWALLS (PIPES, BOX CULVERTS, BOX BRIDGES) SHALL BE ABSORBED IN OTHER ITEMS BID.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING EXISTING STRUCTURES SUCH AS, BUT NOT LIMITED TO PIPES, NLETS, APRONS, AND BRIDGES FROM DAMAGE WHICH MIGHT OCCUR DURING CONSTRUCTION. THE CONTRACTOR SHALL REPLACE OR REPAIR, AS DIRECTED BY THE ENGINEER, ANY STRUCTURES DAMAGED DURING THE LIFE OF THE CONTRACT. NO PAYMENT WILL BE MADE FOR REPLACEMENT OR REPAIR OF DAMAGED ITEMS.

EARTHWORK

- 25% SHRINKAGE FACTOR USED IN THE EARTHWORK CALCULATIONS IS FOR DESIGN ESTIMATING PURPOSES ONLY.
- THE TOP THREE FEET AND VARIABLE OF THE DESIGN SOILS (BOTH NATURAL AND EMBANKMENT) SHALL BE CONSTRUCTED OF SOIL WITH A PERCENT (%) VOLUME CHANGE OF 50 OR LESS AND A CBR OF 5 OR GREATER.
- VOIDS CREATED BY THE REMOVAL OF, BUT NOT LIMITED TO, POSTS, CONCRETE ANCHORS, AND FOOTINGS SHALL BE BACKFILLED AND TAMPED IN ACCORDANCE WITH SECTION 203 OF THE MISSISSIPPI STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION. THE COST OF WHICH WILL BE ABSORBED IN OTHER ITEMS BID.
- VEGETATIVE MATERIAL WILL BE REMOVED PRIOR TO PLACEMENT OF GRANULAR MATERIAL. THE COST OF WHICH SHALL BE ABSORBED IN OTHER ITEMS BID.
- (10) PRIOR TO EARTHWORK OPERATIONS, THE EXISTING TOP 4" TOPSOIL IS TO BE STRIPPED AND STOCKPILED. AFTER THE GRADING OPERATIONS ARE COMPLETED, SAID TOPSOIL SHALL BE PLACED ON ALL AREAS THAT ARE NOT TO BE PAVED OR OTHERWISE PROTECTED. IN ACCORDANCE WITH SECTION 211 OF THE SPECIFICATIONS. OR THE VEGETATION SCHEDULE (SEE WK. SH. VS-1). EXISTING TOPSOIL AND ALL COSTS ASSOCIATED WITH STRIPPING, HAULING, STOCKPILING, AND PLACEMENT OF THE EXISTING TOPSOIL IS TO BE ABSORBED IN OTHER EARTHWORK ITEMS.

ENVIRONMENTAL & CLEARING

(11) NO TEMPORARY CULVERT STREAM CROSSINGS WILL BE ALLOWED.

EROSION CONTROL - TEMPORARY

- (12) WIRE FENCE BACKING WILL BE REQUIRED FOR ALL SILT FENCE. (SEE WK. NO. ECD-3)
- (13) THE EROSION CONTROL DEVICES REFERENCED IN THESE PLANS ARE A MINIMUM REQUIREMENT. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ENSURE THAT SILT DOES NOT LEAVE THE RIGHT OF WAY OR CONTAMINATE WATERS OF THE U.S. DURING CONSTRUCTION. THE CONTRACTOR SHALL SUBMIT AN EROSION CONTROL PLAN PRIOR TO COMMENCEMENT OF WORK AND MAINTAIN THE PLAN DURING CONSTRUCTION. ANY ADDITIONAL SILT BASINS NOT SHOWN IN THE PLANS SHALL BE INCLUDED IN THE CONTRACTOR'S EROSION CONTROL PLAN PRIOR TO SUBMITTING FOR APPROVAL.
- (14) ALL ITEMS OF WORK ASSOCIATED WITH THE INSTALLATION OF A CONSTRUCTION ENTRANCE SHALL BE ABSORBED IN OTHER ITEMS OF WORK.

PAVEMENT, BASE, AND SHOULD

- THE CONTRACTOR SHALL REPAIR ANY DAMAGE TO THE PAVED OR UNPAVED SHOULDER THAT MIGHT OCCUR DURING CONSTRUCTION. ANY REPAIR TO SHOULDER WILL BE IN ACCORDANCE WITH THE APPLICABLE SECTIONS OF THE MISSISSIPPI STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION. NO PAYMENT WILL BE MADE FOR REPAIR OF DAMAGED SHOULDER.
- TEMPORARY PAVEMENT JOINTS (PAPER JOINTS) SHALL BE EMPLOYED AT ALL LOCATIONS REQUIRING TRAFFIC TO TRAVERSE AN UNEVEN PAVEMENT JOINT. PAPER JOINTS SHALL BE A MINIMUM OF OF 9 FEET IN LENGTH AND SHALL BE ADEQUATELY MAINTAINED.
- WHERE MILLING IS REQUIRED, THE CONTRACTOR SHALL PROVIDE OUTLETS IN THE EXISTING SHOULDERS AT SUFFICIENT INTERVALS TO PREVENT POOLING OR STANDING WATER ON THE MILLED SURFACE. THE COST OF WHICH SHALL BE ABSORBED IN OTHER ITEMS BID.

PLANS

- (18) IF COLORS ARE USED ON PLAN/PROFILE SHEETS. THEY ARE INTENDED TO VISUALLY EASE THE LOCATION OF ELEMENTS FOR USERS OF THESE DRAWINGS. ALTHOUGH THE INTENT IS TO CATEGORIZE EVERYTHING AS EITHER EXISTING OR PROPOSED. IT IS THE END USER'S RESPONSIBILITY TO ENSURE ALL ELEMENTS ARE INTERPRETED CORRECTLY, REGARDLESS OF COLOR.
- ALL ADDENDA TO THESE PLANS WILL BE POSTED TO WWW.MDOT.MS.GOV UNDER THE PROPOSAL ADDENDA COLUMN.BIDDERS ARE ADVISED THAT HARD COPIES OF ANY ADDENDA FOR THIS PROJECT WILL NOT BE MAILED IT IS THE BIDDER'S RESPONSIBILITY TO CHECK AND SEE IF ANY ADDENDA HAVE BEEN POSTED FOR THIS PROJECT.

TRAFFIC CONTROL - PERMANENT

- INSTALLATION DATES SHALL BE CLEARLY WRITTEN IN BOLD BLACK MARKINGS ON THE BACK BOTTOM HALF OF ALL SIGNS WITH A PERMANENT MARKING STICK THAT IS WATERPROOF, FADE RESISTANT AND MARKS ON WET OR DRY SURFACES.
- (21) ALL POST, PIPE, AND I-BEAM LENGTHS IN THESE PLANS ARE ESTIMATES. POST LENGTHS FOR ALL SIGNS SHALL BE VERIFIED IN THE FIELD BY THE CONTRACTOR PRIOR TO FABRICATION.
- (22) ALL EXISTING SIGNS WHICH ARE TO BE REMOVED AS A PART OF THIS PROJECT THAT ARE NOT IN CONFLICT WITH CONSTRUCTION SHALL REMAIN IN PLACE UNTIL NEW SIGNS ARE INSTALLED UNLESS NOTED OR DIRECTED OTHERWISE BY THE PROJECT ENGINEER. ROADWAY SIGNS THAT ARE IN CONFLICT WITH CONSTRUCTION SHALL BE REMOVED AND RELOCATED BY THE CONTRACTOR AS DIRECTED BY THE ENGINEER. THE COST OF WHICH SHALL BE ABSORBED IN OTHER ITEMS BID.
- (23) ALL PERMANENT SIGNS SHALL CONFORM TO THE LATEST EDITION OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.
- (24) ALL SIGN LOCATIONS SHALL BE APPROVED BY THE PROJECT ENGINEER PRIOR TO INSTALLATION.
- THE RETROREFLECTIVE SIGN SHEETING ON PERMANENT GROUND-MOUNTED SIGNS SHALL BE AS FOLLOWS: BROWN BACKGROUND SHEETING ON GUIDE SIGNS SHALL BE MINIMUM TYPE VIII; GREEN AND BLUE BACKGROUND SHEETING ON GUIDE SIGNS SHALL BE MINIMUM TYPE IX: ALL WHITE, YELLOW, FLUORESCENT YELLOW AND FLUORESCENT YELLOW/GREEN SHEETING SHALL BE TYPE XI. ALL SIGN SHEETING ON OVERHEAD SIGNS SHALL BE TYPE XI.
- (26) ALL EXISTING SIGNS AND SUPPORTS REMOVED UNDER THIS PROJECT SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND ARE NOT A SEPARATE PAY ITEM.
- (27) ALL SIDE ROAD, STOP SIGN MOUNTED STREET NAME SIGNS TO BE SALVAGED AND STORED AT THE DIRECTION OF THE PROJECT ENGINEER FOR DELIVERY TO THE COUNTY (NOT A SEPARATE PAY ITEM).
- (28) REMOVAL OF RAISED PAVEMENT MARKERS THAT ARE IN CONFLICT WITH REQUIRED CONSTRUCTION IS NOT CONSIDERED A SEPARATE PAY ITEM. COST TO BE ABSORBED IN OTHER ITEMS BID.





22/301000

WK. NO. GN-2

SHEET NO.

GENERAL NOTES (CONT.)

TRAFFIC CONTROL - TEMPORARY

- (29) THE LOCATION AND SPACING OF SIGNS, SHOWN ON THE TRAFFIC CONTROL PLANS, ARE APPROXIMATE AND MAY BE ADJUSTED AS NECESSARY TO FIT FIELD CONDITIONS.
- (30) ALL TRAFFIC CONTROL DEVICES ON THIS PROJECT SHALL COMPLY WITH PART VI OF THE *MUTCD* (LATEST EDITION).
- (31) ALL PLASTIC DRUMS SHALL HAVE A BALLASTING COLLAR MADE FROM RECYCLED TRUCK TIRES OR OTHER SUITABLE MATERIAL
- (32) FLUORESCENT ORANGE SHEETING SHALL BE USED ON ALL CONSTRUCTION AND TRAFFIC CONTROL SIGNS EXCEPT FOR THOSE DESIGNATED ON THE PLANS TO BE BLACK LEGEND AND BORDER ON WHITE BACKGROUND.
- (33) THE CONTRACTOR SHALL COORDINATE WITH THE CONTRACTOR FROM ADJACENT PROJECT(S) IN IMPLEMENTING THE TRAFFIC CONTROL PLAN AS DIRECTED BY THE ENGINEER. ALL CONFLICTING SIGNS SHALL BE COVERED OR REMOVED AS DIRECTED BY THE ENGINEER.
- (34) THE CONTRACTOR SHALL COVER OR REMOVE ANY TEMPORARY TRAFFIC CONTROL SIGNS SHOWN IN THE TRAFFIC CONTROL PLAN THAT DO NOT APPLY TO THE CURRENT PHASE.
- (35) THE RETROREFLECTIVE SIGN SHEETING ON RIGID, TEMPORARY TRAFFIC CONTROL (ORANGE) SIGNS SHALL BE MINIMUM TYPE IX.
- TEMPORARY STRIPING SHALL CONFORM TO FINISHED STRIPE SPECIFICATIONS FOR ALIGNMENT, NEATNESS, AND STRAIGHTNESS.

UTILITIES

- UTILITIES ON THE DRAWINGS ARE SHOWN IN THEIR ORIGINAL LOCATION BASED UPON THE BEST INFORMATION AVAILABLE TO THE ENGINEER CAN NOT AND DOES NOT WARRANT THAT THIS INFORMATION IS COMPLETE OR ACCURATE. THE CONTRACTOR MUST COORDINATE DIRECTLY WITH THE INVOLVED UTILITY OWNERS TO HAVE UNDERGROUND UTILITY LINES FIELD LOCATED IN ADVANCE OF CONSTRUCTION.
- (38) FOR LIST OF PUBLIC UTILITIES, SEE WORKING NO. 3RT.

MISCELLANEOUS

- SOME WORK IS REQUIRED OUTSIDE THE PROJECT LIMITS. NO ADDITIONAL COMPENSATION WILL BE MADE FOR SUCH WORK EXCEPT AS PROVIDED BY SPECIFIC PAY ITEMS INCLUDED IN THE PLANS.
- (40) THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING AND RELOCATING MAIL BOXES AS NECESSARY TO MAINTAIN CONTINUOUS MAIL SERVICE THROUGHOUT THE LIFE OF THE PROJECT. THE COST OF WHICH SHALL BE ABSORBED IN OTHER ITEMS BID.
- (41) THE CONTRACTOR IS RESPONSIBLE FOR FIELD-VERIFICATION OF EXISTING GRADES AND MAKING ADJUSTMENTS AS NECESSARY WITH THE APPROVAL OF THE PROJECT ENGINEER.
- (42) THE CONTRACTOR SHALL COORDINATE AND CONDUCT WORK AT LOCAL ROADS AND DRIVEWAYS IN A MANNER SUCH THAT ACCESS IS NOT INTERRUPTED UNNECESSARILY. ACCESS SHALL BE PRESERVED IN THE BEST MANNER POSSIBLE. COORDINATION AND COMMUNICATION WITH LANDOWNERS MAY BE NECESSARY TO PREVENT INTERRUPTION OF DRIVEWAY ACCESS.
- (43) THE CONTRACTOR SHALL REMOVE ANY EXCESSIVE OVERSPRAY AS DIRECTED BY THE ENGINEER AT NO ADDITIONAL COST TO THE STATE.
- (44) THE SLOTTED CURB WILL REQUIRE TO COATS OF WHITE TRAFFIC PAINT WITH GLASS BEADS REQUIRED IN THE TOP COAT. THIS WORK SHALL BE PAID FOR UNDER PAY ITEM 626-G004.

THE NOTES CONTAINED HEREON ARE SPECIFIC TO THE SUBJECT PROJECT AND SHOULD BE REVIEWED IN DETAIL BY THE CONTRACTOR, PER SECTION 102,05 OF THE STANDARD SPECIFICATIONS, "THE BIDDER IS REQUIRED TO EXAMINE CAREFULLY THE SITE OF THE PROPOSED WORK, THE PROPOSAL, PLANS, STANDARD SPECIFICATIONS, SPECIAL PROVISIONS. NOTICES TO BIDDERS AND CONTRACT FORMS BEFORE SUBMITTING A PROPOSAL."